

Tadpole Spike



image shows optional snoot

Order Code	Tadpole Spike.finish.optic.colour temp
Example	Tadpole Spike.alu.60° reflector.6500K

- Materials: Aluminium
- Lamp: MSL Star
- IP rating: IP66
- Finish: Anodised aluminium
- Dimming: 1-10V, DMX, DALI or Mains Dim
- Supply: Remote driver required
Allow 2.3W at 700mA or 1.1W at 350mA
- Locking: 1.5mm allen key required
- Available tilt: ±90°
- Weight: 0.3kg
- Description: Lockable mini LED spotlight on stainless steel spike
- Accessories: Ø20mm optics or our 60° reflector

Please note all output figures are based on output from bare LED strips/arrays and for indicative purposes only, output will vary when in fittings and as a function of the LED colour and running temperature

LED Information

Each LED “lamp” consists of one or more CREE XRE power LED thermally bonded to an aluminium cored printed circuit board. Colour temperatures of 2800K, 3000K, 3500K, 5000K and 6500K can be specified as can Amber, Red, Green, Blue or any combination of these.



MSL Star
Ø21mm PCB with a single LED. Depending on the luminaire Ø20mm or Ø27mm optics can be used.

For driver information see LED driver spec sheet.

