BPX



See over page for detailled drawings

Order Code	BPX.module.deviation.finish
Example	*BPX.3000K,930lm.bulb.RAL9010*

Materials:	Aluminium, acrylic
Lamp:	Xicato XSM or XIM LED Module
Output:	See module compatibility chart available to download from our website
CRI Ra:	≥80 or ≥95 Artist
Finish:	Anodised aluminium or painted to any RAL colour
Dimming:	1-10V, DMX, DALI or Mains Dim
Driver:	Remote driver required
Weight:	Variable
Description:	Modular system with various accessories/deviations available based on core puck

Xicato Thermal Validation Programme approved

LED Information


This product uses the Xicato Module

Technical advantages of the Xicato Module:


- Colour consistency Initial; 1 x 2 SDCM
- Colour consistency Maintained; 3 SDCM
- Excellent colour rendering
- Uniform beam
- No multiple shadowing


For more information about the modules available please ask sales@mikestoanelighting.com for a current technical data sheet or visit www.xicato.com


Dimensions with XSM Module




NOT TO SCALE.
EXPLODED VIEW FOR USE WITH ACCESSORIES AS SHOWN BELOW.








Dimensions with XIM Module





MIKE STOANE LIGHTING I EQUIPMENT DESIGN + MANUFACTURE I www.mikestoanelighting.com