


ADL.CP Type M



Order Code	ADL.CP.M.col temp.optic.finish
Example	ADL.CP.M.3000K.18°.RAL9010




- Materials: Aluminium, stainless steel cover plate
- Lamp: Type M (3 x Cree XPE)
- Finish: Cover and OD of lamp case painted to any RAL colour, ID of lamp case black.
- Dimming: 1-10V or DMX
- Supply: Remote driver required
Allow 6.9W at 700mA, 3.2W at 350mA
- Locking: Requires 3mm allen key
- Weight: 0.3 kg
- Cut out: Ø95
- Tilt angle: 38°
- Description: Adjustable and lockable LED downlight with magnetic cover plate to conceal fixings
- Accessories: 10°, 18°, 34° or 54° optics

Please note all output figures are based on output from bare LED strips/arrays and for indicative purposes only, output will vary when in fittings and as a function of the LED colour and running temperature

LED Information

The Type M "lamp" consists of three CREE XPE power LED thermally bonded to an aluminium cored printed circuit board. Colour temperatures of 2800K, 3000K, 3500K, 5000K and 6500K can be specified as can Amber, Red, Green, Blue or any combination of these.



Type M
Ø49mm PCB with three LEDs on a single circuit. For XPE optics.

For driver information see LED driver spec sheet.
For more optic information see Optic spec sheet.