

Project Title: _____

Luminaire Ref: _____

 Press to send

Send form to whitegoods



plaster-in

Product Codes & Description (Ordering information)						
Frame	Led module	Beam °	Diffuser	Dimming	Voltage	Emergency
P60SWW* plaster-in	XI-H-830-1070* 80 CRI 12.9W Up to 1070 lm	Xicato 40°*	FRG* frosted glass	ND non-dim 0-10V 0-10 Volt dim 1-10V 1-10 Volt dim TR trailing edge dim DALI DALI protocol	220-240V standard 120-277V universal	EMND non-dim EMST self-test EMDA DALI
	XI-830-780* 80 CRI 8.8W Up to 780 lm	56°				
	XI-H-930-700* 95 CRI 12.4W Up to 700 lm	Citiled 19°*				
	XI-930-500* 95 CRI 8.5W Up to 500 lm	41°*				
	CL-930-1000* 97 CRI 13W Up to 1000 lm					
* Items available for Quickship						

Product Description
60mm rectangular recessed luminaire with trimless ‘plaster-in’ for absolute minimal visual impact. Wall wash fixture are IP65 rated luminaires.

Finish
Standard product finish is white powder coated RAL 9010 with 30% gloss.

Cut-out
78 x 80mm

Example LED module codes
XI-830-1070
XI = Xicato
830 = 80CRI, 3000K colour temperature
1070 = up to 1070 lumen package

XI-927-700
XI = Xicato
927 = 95CRI, 2700K colour temperature
700 = up to 700 lumen package

CL-830-1300
CL = Citiled
830 = 80CRI, 3000K colour temperature
1300 = up to 1300 lumen package

Examples of typical output options
Module XI-827/830/840
Run @ 500mA = 1070lm, 12.9W (see detail a)
Run @ 350mA = 780lm, 8.8W (see detail b)

Module XI-927/930/940
Run @ 500mA = 700lm, 12.4W (see detail a)
Run @ 350mA = 500lm, 8.5W (see detail b)

Module CL-827/830/840
Run @ 350mA = 1300lm, 13.2W (see detail b)

Dimming

- ND: non-dimming
- 0-10V: 0-10 Volt dimming, min 0.1%
- 1-10V: 1-10 Volt dimming, min 0.1%
- TR: trailing edge dimming
- DALI: DALI protocol, min 0.1%


All drivers are suitable for remote mounting up to 10 meters from fixture. Longer distances are available on request. Additional ceiling depths apply with certain drivers, contact Whitegoods for further details.

Emergency
EMND: emergency non-dimmable
EMST: emergency self-test
EMDA: emergency DALI protocol

Accessories
AG-50-C: clear glass

Notes

- Manufacturing LED module detail shown. Refer to photometry data for LM79-08 results.
- All LED modules available in 2700, 3000, 3500 and 4000 Kelvin.
- Xicato and Citiled modules can be underrun.
- Luminaires rated at 40°C maximum ambient temperature.
- Product code containing ‘H’ has a higher frame (140mm) see detail a.
- Minimum ceiling depths for emergency system is required , contact Whitegoods for further details.



Specifier Details

