

60 Square Ceiling Wash LED

whitegoods

Project Title: _____

Luminaire Ref: _____

 Press to send



Send form to whitegoods



plaster-in



bezel



Product Codes & Description (Ordering information)				
Frame	Led module	Dimming	Voltage	Emergency
P60SCFW* plaster-in B60SCFW* bezel	CL-830-350 80 CRI 3.2W 350 lm	ND non-dim 0-10V 0-10 Volt dim 1-10V 1-10 Volt dim TR trailing edge dim DALI DALI protocol	220-240V standard 110V universal	EMND non-dim EMST self-test EMDA DALI

* Items available for Quickship

Product Description
A 60mm high level ceiling wash luminaire with absolute minimal visual impact.

Finish
Standard product finish is white powder coated RAL 9010 with 30% gloss.

Cut-out
70 x 70 mm
Fixture requires 80mm wall gap for installation.



Example LED module codes
CL-830-350
CL = Citiled
830 = 80CRI, 3000K colour temperature
350 = up to 350 lumen package

Examples of typical output options
Module CL-827/830/840
Run @ 350mA = 335lm, 3.2W

Dimming

- ND: non-dimming
- 0-10V: 0-10 Volt dimming, min 0.1%
- 1-10V: 1-10 Volt dimming, min 0.1%
- TR: trailing edge dimming
- DALI: DALI protocol, min 0.1%

All drivers are suitable for remote mounting up to 10 meters from fixture. Longer distances are available on request. Additional ceiling depths apply with certain drivers, contact Whitegoods for further details.

Emergency
EMND: emergency non-dimmable
EMST: emergency self-test
EMDA: emergency DALI protocol

Notes

- Manufacturing LED module detail shown. Refer to photometry data for typical results.
- All LED modules available in 2700, 3000, 3500 and 4000 Kelvin.
- Luminaires rated at 40°C maximum ambient temperature.

Minimum wall gap for emergency system is required , contact Whitegoods for further details.

Specifier Details