

trumpet

RECESSED DOWNLIGHT





Aluminium recessed downlight.

Available in anodised aluminium or painted white RAL9003 tex.

LED source Xicato XSM-XIM.

Available standard in 700 up to 1.300 lm output. Beam option 40° and 60°.




















REF A6068 trumpet

A6069 trumpet white

LED Xicato XSM/XIM

LED LM OUTPUT 700/1.000/1.300 lm

POWER CONS. according to Im output - see table p. 57

COLOR TEMP. 2.700/3.000/4.000 K

CRI/GAI 80 or +95 REFLECTOR 40°/60°

FINISH anodised aluminium / white RAL9003 tex

ADJUSTABLE n/a
CUT-OUT Ø 80 mm

DRIVE CURRENT XSM versions: 1.050 mA

XIM versions: 350/700 mA

MODEL	REFERENCE	LUMEN OUTPUT	CRI / COLOR TEMPERATURE	BEAM	DIMMING OPTION
	A6068 A6069	700 lm 1.000 lm	8027/9527	20° 40°	PD (phase dimming) ND (non dimmable) AD (dall + 1-10V)
			8030/9530		
trumpet			8040/9540		
trumpet white		1.300 lm	8027/9527		
			V80301/8030/9530		
			8040/9540		

ORDER CODE: MODEL Nº + LUMEN OUTPUT + CRI / COLOR TEMPERATURE / GAI + BEAM ANGLE + DIMMING OPTION F.E.: A60**/700lm/8030/40*/ND

V8030': Vibrant series XSM GAI: 111