

common sx

RECESSED DOWNLIGHT

LIGHTSOURCE BY
XICATO

Adjustable square aluminium recessed downlight.


Available in anodised aluminium or painted white

RAL9003 tex.

LED source Xicato XIM.

Available standard in 700 lm output.

Beam option 40° and 60°.



REF A6124A common sx alu

A6124W common sx white

LED Xicato XIM

LED LM OUTPUT 700 lm

POWER CONS. 5,6 W

COLOR TEMP. 2.700/3.000/4.000 K

CRI/GAI 80

REFLECTOR 40°/60°

FINISH anodised aluminium / white RAL9003 tex

ADJUSTABLE 0-30°

CUT-OUT Ø 80 mm with blade springs

DRIVE CURRENT 350 mA

REMARK also available as MR16/GU10 downlight

A2032 common S

A2033 common S white

MODEL	REFERENCE	LUMEN OUTPUT	CRI / COLOR TEMPERATURE	BEAM	DIMMING OPTION
common x alu common x white	A6124A A6124W	700 lm	8027	20° 40°	PD (phase dimming) ND (non dimmable)
			8030		
			8040		

ORDER CODE: MODEL N° + LUMEN OUTPUT + CRI / COLOR TEMPERATURE / GAI + BEAM ANGLE + DIMMING OPTION
 F.E.: A60°/700lm/8030/40°/ND