

fianco

RECESSED DOWNLIGHT

LIGHTSOURCE BY
XICATO


Adjustable aluminium recessed downlight.

Available in painted white RAL9016 tex.

LED source Xicato XSM-XIM.

Available standard in 700 up to 1.300 lm output.

Beam option 40° and 60°.



REF	A6130 fianco
LED	Xicato XSM/XIM
LED LM OUTPUT	700/1.000/1.300 lm
POWER CONS.	according to lm output - see table p. 57
COLOR TEMP.	2.700/3.000/4.000 K
CRI/GAI	80 or +95 / V8030 vibrant
REFLECTOR	40°/60°
FINISH	white RAL9016
ADJUSTABLE	0-30°
CUT-OUT	Ø 95 mm
DRIVE CURRENT	XSM versions: 1.050 mA
	XIM versions: 350/700/1.050 mA

MODEL	REFERENCE	LUMEN OUTPUT	CRI / COLOR TEMPERATURE	BEAM	DIMMING OPTION
fianco	A6130	700 lm 1.000 lm	8027/9527	40° 60°	PD (phase dimming) ND (non dimmable) AD (dali + 1-10V)
			8030/9530		
			8040/9540		
		1.300 lm	8027/9527		
			V8030/8030/9530		
			8040/9540		

ORDER CODE: MODEL N° + LUMEN OUTPUT + CRI / COLOR TEMPERATURE / GAI + BEAM ANGLE + DIMMING OPTION
 F.E.: A60°/700lm/8030/40°/ND

V8030: Vibrant series XSM GAI: 111