

alfa

RECESSED DOWNLIGHT

LIGHTSOURCE BY
XICATO




Cast aluminium downlight.

Available in painted white RAL9016.

LED source Xicato XSM-XIM.

Available standard in 1.300 up to 4.000 lm output.

Beam 52°.



REF A6131 alfa
LED Xicato XSM/XIM
LED LM OUTPUT 1.300/2.000/3.000/4.000 lm
POWER CONS. according to lm output - see table p. 57
COLOR TEMP. 2.700/3.000/4.000 K
CRI/GAI 80 or +95 / V8030 vibrant
REFLECTOR 52°
FINISH white RAL9016
ADJUSTABLE n/a
CUT-OUT Ø 175 mm
DRIVE CURRENT XSM versions: 1.050 mA
XIM versions: 350/700/1.050 mA
REMARK with front glass

MODEL		LUMEN OUTPUT	CRI / COLOR TEMPERATURE	BEAM	DIMMING OPTION
alfa	A6131	1.300 lm 2.000 lm	8027/9527	52°	PD (phase dimming) ND (non dimmable) AD (dali + 1-10V)
			V8030/8030/9530		
			8040/9540		
		3.000 lm	8027		
			V8030/8030		
			8040		
		4.000 lm	8030		ND (non dimmable) AD (dali + 1-10V)
			8040		

ORDER CODE: MODEL N° + LUMEN OUTPUT + CRI / COLOR TEMPERATURE / GAI + BEAM ANGLE + DIMMING OPTION
F.E.: A60**/700lm/8030/40°/ND

V8030': Vibrant series XSM GAI: 111