

# unilite

RECESSED DOWNLIGHT

LIGHTSOURCE BY  
**XICATO**




Adjustable square metal downlight.

Available in white RAL9003 tex.

LED source Xicato XSM-XIM.

Available standard in 1.300 up to 4.000 lm output.

Beam 20°, 40° and 60°.



REF **A6127** unilite

LED Xicato XSM/XIM

LED LM OUTPUT 1.300/2.000/3.000/4.000 lm

POWER CONS. according to lm output - see table p. 57

COLOR TEMP. 2.700/3.000/4.000 K

CRI/GAI 80 or +95 / V8030 vibrant

REFLECTOR 20°/40°/60°

FINISH white RAL9003 tex

ADJUSTABLE 360° x 30°

CUT-OUT 170 x 170 mm

DRIVE CURRENT XSM versions: 1.050 mA

XIM versions: 350/700/1.050 mA

MODEL	REFERENCE	LUMEN OUTPUT	CRI / COLOR TEMPERATURE	BEAM	DIMMING OPTION
unilite	A6127	1.300 lm 2.000 lm	8027/9527	52°	PD ( phase dimming ) ND ( non dimmable ) AD ( dell + 1-10V )
			V8030/8030/9530		
			8040/9540		
		3.000 lm	8027		
			V8030/8030		
			8040		
		4.000 lm	8030		ND ( non dimmable ) AD ( dell + 1-10V )
			8040		

ORDER CODE: MODEL N° + LUMEN OUTPUT + CRI / COLOR TEMPERATURE / GAI + BEAM ANGLE + DIMMING OPTION  
F.E.: A60\*\*/700lm/8030/40°/ND

V8030: Vibrant series XSM GAI: 111