duolite

RECESSED DOWNLIGHT

LIGHTSOURCE BY XICATO

EXTERUS LIGHTOLOGY 5 YEAR WARRANTY



Rectangular double source metal downlight.


Available in white RAL9003 tex.

LED source Xicato XSM-XIM.

Available standard in 1.300 up to 4.000 lm output.

Beam 20°, 40° and 60°.

CE EG-FPC | 170x320 mm cut out | ceiling | indoor | class 3 | IP20 IP rating | LED | F



REF	**A6128** duolite
LED	Xicato XSM/XIM
LED LM OUTPUT	1.300/2.000/3.000/4.000 lm
POWER CONS.	according to lm output - see table p. 57
COLOR TEMP.	2.700/3.000/4.000 K
CRI/GAI	80 or +95 / V8030 vibrant
REFLECTOR	20°/40°/60°
FINISH	white RAL9003 tex
ADJUSTABLE	360° x 30°
CUT-OUT	170 x 320 mm
DRIVE CURRENT	XSM versions: 1.050 mA
	XIM versions: 350/700/1.050 mA

MODEL	REFERENCE	LUMEN OUTPUT	CRI / COLOR TEMPERATURE	BEAM	DIMMING OPTION
duolite	A6128	1.300 lm 2.000 lm	8027/9527	52°	PD (phase dimming) ND (non dimmable) AD (dali + 1-10V)
			V8030[1]/8030/9530		
			8040/9540		
		3.000 lm	8027		
			V8030[1]/8030		
			8040		
		4.000 lm	8030		ND (non dimmable) AD (dali + 1-10V)
			8040		

ORDER CODE: MODEL N° + LUMEN OUTPUT + CRI / COLOR TEMPERATURE / GAI + BEAM ANGLE + DIMMING OPTION
F.E.: A60**/700lm/8030/40°/ND

V8030[1]: Vibrant series XSM GAI: 111