150 Square Wall Wash LED

whitegoods

Project Title: .....

Luminaire Ref: .....

Press to send

Send form to whitegoods



plaster-in

Product Codes & Description (Ordering information)

Frame	LED module	Beam °	Diffuser	Dimming	Voltage	Emergency
P150SWW* plaster-in	**XI-830-3000** 80 CRI 45W Up to 3000 lm **XI-930-2000*** 90 CRI 43.2W Up to 2000 lm	Xicato **14°** **52°***	**FRG*** frosted glass **FRP** frosted polycarbonate **CLG** clear glass **SCG** sculpture glass **MPG** micro prismatic glass	**ND** non-dim **0-10V** 0-10 Volt dim **1-10V** 1-10 Volt dim **TR** trailing edge dim **DALI** DALI protocol	**220-240V** standard **120 - 277V** universal	**EMND** non-dim **EMST** self-test **EMDA** DALI
	CL-830-4000 80 CRI 39.4W Up to 4000 lm **CL-930-3000** 97 CRI 39W Up to 3000 lm	Citiled **12°** **38°** **72°***				

*** Items available for Quickship**

Product Description

A 150 x 225mm rectangular wall wash luminaire trimless 'plaster-in' for absolute minimal visual impact. Available with various adjustable diffusers for flush and regressed applications.


Finish


Standard product finish is white powder coated RAL 9010 with 30% gloss.

Cut-out

170 x 170mm







Example LED module codes

XI-830-2000
XI = Xicato
830 = 80CRI, 3000K colour temperature
2000 = up to 2000 lumen package

XI-927-1300
XI = Xicato
927 = 95CRI, 2700K colour temperature
1300 = up to 1300 lumen package

CL-830-4000
CL = Citiled
830 = 80CRI, 3000K colour temperature
4000 = up to 4000 lumen package

Examples of typical output options

Module XI-827/830/840
Run @ 1050mA = 2000lm, 28.8W
Run @ 700mA = 1420lm, 18.5W

Module XI-927/930/940
Run @ 1050mA = 1300lm, 27.7W
Run @ 700mA = 930lm, 17.8W

Module CL-827/830/940
Run @ 1050mA = 4000lm, 39W
Run @ 700mA = 2800lm, 25W
Run @ 500mA = 2100lm, 17.4W

Dimming

- ND: non-dimming
- 0-10V: 0-10 Volt dimming, min 0.1%
- 1-10V: 1-10 Volt dimming, min 0.1%
- TR: trailing edge dimming
- DALI: DALI protocol, min 0.1% .

All drivers are suitable for remote mounting up to 10 meters from fixture. Longer distances are available on request. Minimum ceiling depths apply, contact Whitegoods for further details.

Emergency

EMND: emergency non-dimmable
EMST: emergency self-test
EMDA: emergency DALI protocol

Notes

- Manufacturing LED module detail shown. Refer to photometry data for LM79-08 results.
- All LED modules available in 2700, 3000, 3500 and 4000 Kelvin.
- Xicato and Citiled modules can be underrun.
- Luminaires rated at 40°C maximum ambient temperature.

Please contact Whitegoods for further LED specifications.

Specifier Details

Whitegoods reserves the right to make technical alterations without notice.

Whitegoods Lighting Ltd Unit 19, Hiltongrove, 14 Southgate Road, London, N1 3LY t: +44 (0) 20 7241 2032 w: www.whitegoods.com e: info@whitegoods.com