

# XACARA™ CL SQ

WEB PIN™ 633



## GENERAL SPECIFICATION

**Body and trim:** Steel and aluminium.

**Array housings:** Die cast aluminium.

**Gimbal:** Fully articulating on two axes.

**Suspension:** Two or four cables, fully adjustable.

**Reflectors:** Highly reflective, specular finish, vacuum plated.

**Protective lens:** Clear glass.

**Power cable:** Silver braided.

**Finish:** Powder coated, as specified.

**Drivers:** HPF electronic for 120-277V. 0-10V dimming (10%).

**Approvals:** ETL/US, ETL/C, CE.

## A SPECIFY LUMINAIRE

Code:	Power:	*Delivered lms:	*Efficacy LPW:	CBCP:	L70 @25°C (77°F):
<b>50 1220</b>	2 x 26W LED	2 x 2085	80	4104	> 60,000
<b>50 1240</b>	4 x 26W LED	4 x 2085	80	4104	> 60,000

## B SPECIFY CCT/CRI

<b>30A</b>	3000K (min 80 CRI)
<b>30B</b>	3000K (min 90 CRI)
<b>35A</b>	3500K (min 80 CRI)
<b>35B</b>	3500K (min 90 CRI)
<b>40A</b>	4000K (min 80 CRI)
<b>40B</b>	4000K (min 90 CRI)

## C SPECIFY REFLECTOR

<b>ME</b>	Medium 36°
<b>XW</b>	Extra wide 70°

## D SPECIFY FINISH

<b>BL</b>	Black
<b>MS</b>	Metallic Silver
<b>WH</b>	White

*\*approx values based on 3000K (min 80 CRI)*

**Example Specification Code:** 50 1220 • 30A • ME • BL

Photometric testing performed using LM79 procedures.

