

# XACARA™ CL-R

WEB PIN™ 613



## GENERAL SPECIFICATION

**Housing:** Die cast aluminium.

**Reflectors:** Medium and wide beam. Highly reflective, specular finish, vacuum plated.

**Protective lens:** Clear glass.

**Finish:** Powder coated, as specified.

**Drivers:** HPF electronic for 120-277V. 0-10V dimming (10%).

**Mounting:** Luminaire mounts to a Jbox. Driver mounts to the inside of the Jbox. Mounting hardware included.

**Approvals:** ETL/US, ETL/C. Damp location.

#### A SPECIFY LUMINAIRE

Code:	Power:	*Delivered lms:	*Efficacy LPW:	L70 @25°C (77°F):
50 1012	26W LED	2085	80	> 60,000 hrs

#### B SPECIFY CCT/CRI

30A	3000K (min 80 CRI)
30B	3000K (min 90 CRI)
35A	3500K (min 80 CRI)
35B	3500K (min 90 CRI)
40A	4000K (min 80 CRI)
40B	4000K (min 90 CRI)

#### C SPECIFY REFLECTORS

ME	Medium 36°
XW	Extra wide 70°

#### D SPECIFY FINISH

BL	Black
MS	Metallic Silver
WH	White

*\*approx values based on 3000K (min 80 CRI)*

**Example Specification Code:** 50 1012 • 30A • ME • MS

Photometric testing performed using LM79 procedures.

