

XACARA™ -L INDIRECT

WEB PIN™ 167



GENERAL SPECIFICATION

Body: Die cast aluminium and steel.

Finish: White powder coated.

Suspension: Two polished chrome plated tubes or three stainless steel cables.

Visible power cable: Silver braided.

Reflectors: Aluminium, specular finish with vertical facets.

Dust cover: Clear polycarbonate.

Drivers: HPF electronic 120-277V, 0-10V dimming standard (10%).

Remote Emergency: Emergency option provides a 1.5 hour emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (maximum distance between wall/ceiling plate and luminaire is 4.5m/15'). Test switch fits a single gang box (not supplied).

Mechanical: Luminaires mount directly over a junction box (not supplied).

Approvals: ETL/US, ETL/C, CE.

INDIRECT ILLUMINATION PENDANT

A SPECIFY LUMINAIRE

Code:	Power:	*Delivered lms:	*Efficacy LPW:	Photometry:
50 3520	140W (4 LEDs)	13631	103	File# 503520
50 3620	175W (5 LEDs)	17009	103	File# 503620

B SPECIFY CCT/CRI

- 30A** 3000K (min 80 CRI)
- 30B** 3000K (min 90 CRI)
- 35A** 3500K (min 80 CRI)
- 35B** 3500K (min 90 CRI)
- 40A** 4000K (min 80 CRI)
- 40B** 4000K (min 90 CRI)

C SPECIFY SUSPENSION

- TS** Tube suspension
- CS** Cable suspension (6 lamp only)

D SPECIFY OPTIONS

- DA** DALI dimming (10%)
- RE** Remote emergency (max distance 15ft. Not available with DALI or 347V)
- CT** Custom tube length (contact factory)
- 3** 347V (not available with Dali)

*approx values based on 3000K (min 80 CRI)

Example Specification Code: 50 3520 • 30A • TS

Photometric testing performed using LM79 procedures.

