

XACARA™ RD

WEB PIN™ 197



GENERAL SPECIFICATION

Body and trim: Steel and aluminium.

Array housings: Die cast aluminium.

Gimbal: Fully articulating on two axes.

Suspension: Three cables, fully adjustable.

Reflectors: Medium and wide beam. Highly reflective, specular finish, vacuum plated.

Protective lens: Clear glass.

Power cable: Silver braided.

Finish: Powder coated, as specified.

Drivers: HPF electronic for 120-277V. 0-10V dimming (10%).

Approvals: ETL/US, ETL/C, CE.

DIRECT/INDIRECT ILLUMINATION PENDANT

A SPECIFY LUMINAIRE

Code:	Power:	*Delivered lms:	*Efficacy LPW:	L70 @25°C (77°F):
50 1030	3 x 26W LED	3 x 2085	80	> 60,000
50 1060	6 x 26W LED	6 x 2085	80	> 60,000

B SPECIFY CCT/CRI

30A	3000K (min 80 CRI)
30B	3000K (min 90 CRI)
35A	3500K (min 80 CRI)
35B	3500K (min 90 CRI)
40A	4000K (min 80 CRI)
40B	4000K (min 90 CRI)

C SPECIFY REFLECTOR

ME	Medium 36°
XW	Extra Wide 70°

D SPECIFY FINISH

BL	Black
MS	Metallic Silver
WH	White

*approx values based on 3000K (min 80 CRI)

Example Specification Code: **50 1030 • 30A • ME • MS**

Photometric testing performed using LM79 procedures.

