

KIORA™ II DISC

WEB PIN™ 125



GENERAL SPECIFICATION

Diffuser: Injection moulded opal acrylic with an etched lower band.

Suspension: Twin stainless steel cables.

Power cable: Silver braided.

Disc: Aluminum plate.

Finish: Metallic silver powder coated paint.

Reflector (optional): Aluminum, frosted finish with vertical facets.

Drivers: HPF electronic, 120/277V. 0-10V, 1% dimming standard.

Remote emergency system: Emergency option provides a 1.5 hour emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (maximum distance between wall/ceiling plate and luminaire is 4.5m/15'). Test switch fits a single gang box (not supplied).

Mechanical: Mounts directly to a junction box (by others). Mounting hardware (by others).

Approvals: ETL.

A SPECIFY LUMINAIRE

Code:	Power:	*Delivered lms:	*Efficacy LPW:	L70 @25°C (77°F):	Weight:	Photometry:
44 1101	30W LED	1920	70.3	> 50,000 hrs	11Kg/24lb	File# 441101

B SPECIFY CCT

30 3000K (min 80 CRI)
35 3500K (min 80 CRI)
40 4000K (min 80 CRI)

C SPECIFY DISC FINISH

WH White
BL Blue
MS Metallic silver
OT Other painted finish (please specify an RAL number)

D SPECIFY OPTIONS

RF Internal faceted reflector
3 347V
RE Remote emergency
L2 Hilume 1% H Ecosystem LED

*approx values based on 3000K (min 80 CRI)

Example Specification Code: 44 1101 • 30 • WH

