XACARA™

WEB PIN™ 274



GENERAL SPECIFICATION

Body: Die cast aluminum.
Finish: Powder coated.
Suspension: Single stainless steel aircraft cable or steel tube.
Power cable: Clear with silver wires.
Reflectors: Aluminum, specular finish with multiple facets**.**
Protective lens: Clear glass.
Drivers: HPF electronic, 120/277V with 0-10V dimming (1%).
Approvals: ETL/US, ETL/C, CE.

© 2017 BETA-CALCO INC.
BETACALCO.COM

A SPECIFY LUMINAIRE

Code:	Power:	*Delivered lms:	*Efficacy LPW:	L70 @25°C (77°F):
50 1000	11W **LED**	862	78	> 60,000
50 1002	15W **LED**	1143	76	> 60,000
50 1004	26W **LED**	2085	80	> 60,000

B SPECIFY CCT

30 3000K (min 80 CRI)
35 3500K (min 80 CRI)
40 4000K (min 80 CRI)

C SPECIFY REFLECTOR

ME Medium 36°
XW Extra wide 70°

D SPECIFY FINISH

BL Black
MS Metallic Silver
WH White

E SPECIFY SUSPENSION

CS Cable suspension
TS3 Tube 457mm/18"
TS4 Tube 610mm/24"
TS5 Tube 762mm/30"
TS6 Tube 914mm/36"
TS7 Tube 1067mm/42"
TS8 Tube 1220mm/48"


F SPECIFY OPTIONS


DZ 0-10V dimming 0%
DL DALI dimming 1%
DA DALI dimming 0.1%
L1 Lutron L3DA3W Hi lume 1%
L3 Lutron L3DAE Hi lume 1% EcoSystem

**approx values based on 3000K (min 80 CRI)*

Example Specification Code: **50 1000 ▪ 30 ▪ ME ▪ BL ▪ CS**

Photometric testing performed using LM79 procedures.





The XACARA line of products are the subject of several pending U.S. Design Patent and Canadian Industrial Design Applications. EU Registered Design Application Pending.

Note: *Due to constant changes in LEDs, please check our website for current product specifications.*

© 2017 BETA-CALCO INC.