



GENERAL SPECIFICATION

Body and trim: Aluminum and steel.

Suspension: Single tube with three cables or three cables only.

Finish: WH & MS, all metalwork powder coated. BA, main body brushed aluminum; canopy and suspension tube satin chrome plated to match.

Dust cover: Clear polycarbonate.

Internal rebound reflector: Gloss white, powder coated.

Power cable: Silver braided.

Drivers: HPF electronic for 120-277V, 0-10V, 10% dimming standard.

Mechanical: Luminaire mounts directly over a junction box.

Remote emergency system: Emergency option provides a 1.5 hour emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (maximum distance between wall/ceiling plate and luminaire is 4.5m/15'). Test switch fits a single gang box (not supplied).

Approvals: ETL.

A SPECIFY LUMINAIRE

Code:	Power:	*Delivered lms:	*Efficacy LPW:	Diameter (A):	Height (H):	Photometry:
77 2305	42W LED	5052	119	584mm/23"	521mm/20.5"	File# 772305
77 2905	85W LED	10151	120	737mm/29"	648mm/25.5"	File# 772905
77 3605	127W LED	15266	120	914mm/36"	800mm/31.5"	File# 773605
77 4205	169W LED	20615	122	1067mm/42"	800mm/31.5"	File# 774205

B SPECIFY CCT

30	3000K (min 80 CRI)
35	3500K (min 80 CRI)
40	4000K (min 80 CRI)

C SPECIFY SUSPENSION

TS	Tube suspension
CS	Cable suspension

D SPECIFY FINISH

WH	White
MS	Metallic silver
BA	Brushed aluminium
OT	Other painted finish <i>(please specify an RAL number)</i>

E SPECIFY OPTIONS

RE	Remote emergency <i>(max distance 10 ft)</i>
DA	DALI drivers

*approx values based on 3000K (min 80 CRI)

Example Specification Code: **77 2305 - 30 - TS - MS**

