

BELARO™ REFLECTOR

WEB PIN™ 110



Decorative Options



GENERAL SPECIFICATION

Body and trim: Steel and aluminum.

Finish: Powder coated metallic silver.

Suspension: Twin aircraft cables (optional tubes for CFL).

Power cable: Silver braided.

Reflector: High purity aluminum, specular finish with vertical facets.

Upper diffuser: UV stabilized acrylic.

Decorative disc: 6mm/1 4" glass with a polished edge and a sandblasted finish.

Decorative ring: 6mm/1 4" green tint, acrylic (faux glass) with a polished edge and a sandblasted finish.

Drivers: Luminaires supplied with HPF electronic drivers, 120/277V. 0-10V dimming standard (10%).

Remote emergency: Emergency option provides a 1.5 hour emergency lighting facility. The remote system includes the inverter module, NiCad batteries and a remote wall/ceiling LED charge indicator and test switch (maximum distance between wall/ceiling plate and luminaire is 4.5m/15'). Test switch fits a single gang box (not supplied).

Mechanical: Luminaires mount to a junction box (by others).

Approvals: ETL.

A SPECIFY LUMINAIRE

Code:	Power:	*Delivered lms:	*Efficacy LPW:	L70 @25°C (77°F):	Weight:	Height (H):	Diameter (D):	Photometry:
20 1270	30W LED	2020	72.1	> 50,000 hrs	9Kg/20lb	520mm/13"	318mm/12.5"	File# 201270
20 1801	57W LED	3997	70.0	> 50,000 hrs	9Kg/20lb	559mm/22"	406mm/16"	File# 201801
20 2250	70W LED	5995	70.0	> 50,000 hrs	10Kg/22lb	686mm/27"	559mm/22"	File# 202250
20 2254	100W LED	7994	70.0	> 50,000 hrs	11Kg/24lb	686mm/27"	559mm/22"	File# 202254

B SPECIFY CCT

30	3000K (min 80 CRI)
35	3500K (min 80 CRI)
40	4000K (min 80 CRI)

C SPECIFY REFLECTOR

FR	Full reflector
HG	Half reflector/opal diffuser

D SPECIFY OPTIONS

BL	Blue diffuser
DR	Decorative disc (suspended by four cradle bars)
DS	Decorative disc (suspended by four spacers)
RG	Decorative ring (suspended by four cradle bars)
RR	Decorative ring (suspended by four spacers)
3	347 (22" diameter only)
RE	Remote emergency (max distance 15', 120/277V)

*approx values based on 3000K (min 80 CRI)

Example Specification Code: **20 1270 • 30 • FR**

