

SENTIS™ EQ

WEB PIN™ 501



SB Satin Brass finish

SN Satin Nickel finish

GENERAL SPECIFICATION

Housing: Die-formed steel.

Horizontal bars: Die-cast zinc.

Finish: Powder coated paint or plated.

Reflector: Aluminum, white powder coated.

Front diffuser: UV stabilized polycarbonate with vertical ribs.

Rear side (halo) diffuser: Extruded opal acrylic.

Upper and lower dust covers: Opal polycarbonate.

Drivers: HPF, electronic for 120-277V. LED 0-10V dimming (10%) standard.

Mechanical: Mounts directly to a standard electrical junction box (by others). Additional mounting points provided. Mounting hardware (by others).

Approvals: ETL.

A SPECIFY LUMINAIRE

Code:	Power:	*Delivered lms:	*Efficacy LPW:	Type (A):	Type (B):	Photometry:
32 6141	14W LED	1311	93	356mm/14"		File# 326141
32 6145	20W LED	1865	95	457mm/18"		File# 326145
32 6143	28W LED	2592	94	610mm/24"		File# 326143
32 6146	47W LED	4333	92		914mm/36"	File# 326146
32 6147	59W LED	5323	94		1217mm/48"	File# 326147

B SPECIFY CCT

30	3000K (min 80 CRI)
35	3500K (min 80 CRI)
40	4000K (min 80 CRI)

C SPECIFY FINISH

WH	White
MS	Metallic silver
MB	Metallic bronze
SN	Satin nickel
PB	Polished brass
SB	Satin brass
AB	Antique brass
PC	Polished chrome
CP	Polished copper
CS	Satin copper
AC	Antique copper
OT	Other painted finish (please specify an RAL number)

*approx values based on 3000K (min 80 CRI)

Example Specification Code: **32 6143 • 30 • MS**

