

ERELLA™

WEB PIN™ 649



PC Polished Chrome

GENERAL SPECIFICATION

Body and trim: Steel and aluminum.

Finish: Back plate, powder coated gloss white. Trim, powder coated or plated as listed.


Diffusers: Opal acrylic or UV stabilized polycarbonate.

Drivers: HPF electronic for 120-277V. 0-10V dimming (10%).


Luminaire orientation: Ceiling or wall mounted (29" diameter, ceiling only).

Mechanical: Mounts directly to a junction box (by others).

Approvals: ETL.



MULTI-ARM
WEB PIN™ 393



RECESSED
WEB PIN™ 406




PENDANT
WEB PIN™ 278

A SPECIFY LUMINAIRE

Code:	Power:	*Delivered lms:	*Efficacy LPW:	Diameter (A):	Depth (D):	Weight:	Photometry:
60 0300	30W LED	1500	51.7	457mm/18"	101mm/4"	3.7Kg/8.1lb	File# 600300
60 0400	30W LED	1500	48.8	584mm/23"	101mm/4"	4.5Kg/9.9lb	File# 600400
60 0410	40W LED	1884	48.8	584mm/23"	101mm/4"	4.5Kg/9.9lb	File# 600410

B SPECIFY CCT/CRI

30	3000K (min 80 CRI)
35	3500K (min 80 CRI)
40	4000K (min 80 CRI)



C SPECIFY DIFFUSER

OP	Opal acrylic
PL	Opal polycarbonate
FB	Beige faux alabaster
FW	White faux alabaster

D SPECIFY FINISH

WH	White
MB	Metallic bronze
MS	Metallic silver
PB	Polished brass
SB	Satin brass
AB	Antique brass
PC	Polished chrome
CP	Polished copper
CS	Satin copper
AC	Antique copper
SN	Satin nickel
OT	Other painted finish
<i>(please specify an RAL number)</i>	

*approx values based on 3000K (min 80 CRI)

Example Specification Code: 60 0300 • 30 • OP • PB