
DOMINO 1 RECESSED


NARROW SPOT




Category Interior use only IP20
Material Machined Aluminium
Finish Brushed Aluminium I Black I White I Custom
Cutout ø44mm
Ceiling Thickness 5-25mm
Minimum Ceiling Void 20mm above top of luminaire module
Accessories Lenses
System Power 2.2W
Module Output 178lm
Absolute Output 164lm
LOR 93%
Colour Temperature 3000K*
CRI 95
Optics 12°
Gear Type Dimmable options available
Weight 58g

* Please enquire as to the availability of non-standard colour temperatures.









Domino 1 Recessed is a 95CRI architectural luminaire. The minimal aesthetic, common across the Precision portfolio, ensures the luminaire blends into its architectural surroundings. The luminaire comes as standard in white, black and brushed aluminium finishes, and has five changeable optics for flexible distribution. The built-in, anti-reflective, magnetic accessory holder enables glare control and accommodates accessories up to 9mm thick. Domino 1 Recessed is machined from aerospace grade 6063-T6 aluminium, delivering a lumen package of 178lm at 2.2W.

Product Photometry independently tested in accordance with LM-79







Bezel

	TX-651-AL-309512
	TX-651-BK-309512
	TX-651-WH-309512

PRECISION LIGHTING

SALES@PRECISIONLIGHTING.CO.UK
WWW.PRECISIONLIGHTING.CO.UK

42 RIVERSIDE ROAD
LONDON SW17 0BA
t. +44 (0) 20 8947 6616
f. +44 (0) 20 8286 6626


DOMINO 1 RECESSED


FLOOD




Category Interior use only IP20
Material Machined Aluminium
Finish Brushed Aluminium I Black I White I Custom
Cutout ø44mm
Ceiling Thickness 5-25mm
Minimum Ceiling Void 20mm above top of luminaire module
Accessories Lenses
System Power 2.2W
Module Output 178lm
Absolute Output 150lm
LOR 84%
Colour Temperature 3000K*
CRI 95
Optics 30°
Gear Type Dimmable options available
Weight 58g

* Please enquire as to the availability of non-standard colour temperatures.









Domino 1 Recessed is a 95CRI architectural luminaire. The minimal aesthetic, common across the Precision portfolio, ensures the luminaire blends into its architectural surroundings. The luminaire comes as standard in white, black and brushed aluminium finishes, and has five changeable optics for flexible distribution. The built-in, anti-reflective, magnetic accessory holder enables glare control and accommodates accessories up to 2mm thick. Domino 1 Recessed is machined from aerospace grade 6063-T6 aluminium, delivering a lumen package of 178lm at 2.2W.

Product Photometry independently tested in accordance with LM-79







Bezel

TX-651-AL-309530

TX-651-BK-309530

TX-651-WH-309530

PRECISION LIGHTING
SALES@PRECISIONLIGHTING.CO.UK
WWW.PRECISIONLIGHTING.CO.UK
42 RIVERSIDE ROAD
LONDON SW17 0BA
t. +44 (0) 20 8947 6616
f. +44 (0) 20 8286 6626


DOMINO 1 RECESSED


WIDE FLOOD




Category Interior use only IP20
Material Machined Aluminium
Finish Brushed Aluminium I Black I White I Custom
Cutout ø44mm
Ceiling Thickness 5-25mm
Minimum Ceiling Void 20mm above top of luminaire module
Accessories Lenses
System Power 2.2W
Module Output 178lm
Absolute Output 163lm
LOR 92%
Colour Temperature 3000K*
CRI 95
Optics 60°
Gear Type Dimmable options available
Weight 58g

* Please enquire as to the availability of non-standard colour temperatures.









Domino 1 Recessed is a 95CRI architectural luminaire. The minimal aesthetic, common across the Precision portfolio, ensures the luminaire blends into its architectural surroundings. The luminaire comes as standard in white, black and brushed aluminium finishes, and has five changeable optics for flexible distribution. The built-in, anti-reflective, magnetic accessory holder enables glare control and accommodates accessories up to 2mm thick. Domino 1 Recessed is machined from aerospace grade 6063-T6 aluminium, delivering a lumen package of 178lm at 2.2W.

Product Photometry independently tested in accordance with LM-79







Bezel

	TX-651-AL-309560
	TX-651-BK-309560
	TX-651-WH-309560

PRECISION LIGHTING

SALES@PRECISIONLIGHTING.CO.UK
WWW.PRECISIONLIGHTING.CO.UK

42 RIVERSIDE ROAD
LONDON SW17 0BA
t. +44 (0) 20 8947 6616
f. +44 (0) 20 8286 6626


DOMINO 1 RECESSED


ELLIPSE




Category Interior use only IP20
Material Machined Aluminium
Finish Brushed Aluminium I Black I White I Custom
Cutout ø44mm
Ceiling Thickness 5-25mm
Minimum Ceiling Void 20mm above top of luminaire module
Accessories Lenses
System Power 2.2W
Module Output 178lm
Absolute Output 163lm
LOR 92%
Colour Temperature 3000K*
CRI 95
Optics 12X35°
Gear Type Dimmable options available
Weight 58g

* Please enquire as to the availability of non-standard colour temperatures.









Domino 1 Recessed is a 95CRI architectural luminaire. The minimal aesthetic, common across the Precision portfolio, ensures the luminaire blends into its architectural surroundings. The luminaire comes as standard in white, black and brushed aluminium finishes, and has five changeable optics for flexible distribution. The built-in, anti-reflective, magnetic accessory holder enables glare control and accommodates accessories up to 2mm thick. Domino 1 Recessed is machined from aerospace grade 6063-T6 aluminium, delivering a lumen package of 178lm at 2.2W.

Product Photometry independently tested in accordance with LM-79





Bezel

	TX-651-AL-3095E1
	TX-651-BK-3095E1
	TX-651-WH-3095E1

PRECISION LIGHTING
SALES@PRECISIONLIGHTING.CO.UK
WWW.PRECISIONLIGHTING.CO.UK
42 RIVERSIDE ROAD
LONDON SW17 0BA
t. +44 (0) 20 8947 6616
f. +44 (0) 20 8286 6626


DOMINO 1 RECESSED


VERTICAL ELLIPSE




Category Interior use only IP20
Material Machined Aluminium
Finish Brushed Aluminium I Black I White I Custom
Cutout ø44mm
Ceiling Thickness 5-25mm
Minimum Ceiling Void 20mm above top of luminaire module
Accessories Lenses
System Power 2.2W
Module Output 178lm
Absolute Output 163lm
LOR 92%
Colour Temperature 3000K*
CRI 95
Optics 35X12°
Gear Type Dimmable options available
Weight 58g

* Please enquire as to the availability of non-standard colour temperatures.









Domino 1 Recessed is a 95CRI architectural luminaire. The minimal aesthetic, common across the Precision portfolio, ensures the luminaire blends into its architectural surroundings. The luminaire comes as standard in white, black and brushed aluminium finishes, and has five changeable optics for flexible distribution. The built-in, anti-reflective, magnetic accessory holder enables glare control and accommodates accessories up to 2mm thick. Domino 1 Recessed is machined from aerospace grade 6063-T6 aluminium, delivering a lumen package of 178lm at 2.2W.

Product Photometry independently tested in accordance with LM-79







Bezel

	TX-651-AL-3095E2
	TX-651-BK-3095E2
	TX-651-WH-3095E2

PRECISION LIGHTING
SALES@PRECISIONLIGHTING.CO.UK
WWW.PRECISIONLIGHTING.CO.UK
42 RIVERSIDE ROAD
LONDON SW17 0BA
t. +44 (0) 20 8947 6616
f. +44 (0) 20 8286 6626