

Category Interior use only IP20

Material Machined Aluminium

Finish Brushed Aluminium

System Basis Track

Accessories Lenses

System Power 2.5W

Module Output 178lm

Absolute Output 164lm

LOR 93%

Colour Temperature 3000K*


CRI 95

Optics 12°

Gear Type Dimmable options available


Weight 141g

* Please enquire as to the availability of non-standard colour temperatures.







































RT-651-AL-309519



PRECISION LIGHTING

SALES@PRECISIONLIGHTING.CO.UK

42 RIVERSIDE ROAD LONDON SW17 OBA



Category Interior use only IP20

Material Machined Aluminium

Finish Brushed Aluminium

System Basis Track

Accessories Lenses

System Power 2.5W

Module Output 178lm

Absolute Output 150lm

LOR 84%

Colour Temperature 3000K*


CRI 95

Optics 30°


Gear Type Dimmable options available

Weight 141g

* Please enquire as to the availability of non-standard colour temperatures.







































Basis Track

RT-651-AL-309530



PRECISION LIGHTING

SALES@PRECISIONLIGHTING.CO.UK

42 RIVERSIDE ROAD LONDON SW17 OBA



Category Interior use only IP20

Material Machined Aluminium

Finish Brushed Aluminium

System Basis Track

Accessories Lenses

System Power 2.5W

Module Output 178lm **Absolute Output 163lm**

LOR 92%

Colour Temperature 3000K*

CRI 95


Optics 60°

Gear Type Dimmable options available

Weight 141g

* Please enquire as to the availability of non-standard colour temperatures.

Product Photometry independently tested in accordance with LM-79




















Accessories
















Basis Track

RT-651-AL-309560



PRECISION LIGHTING

SALES@PRECISIONLIGHTING.CO.UK

42 RIVERSIDE ROAD LONDON SW17 OBA

ELLIPSE



Category Interior use only IP20

Material Machined Aluminium

Finish Brushed Aluminium

System Basis Track

Accessories Lenses

System Power 2.5W

Module Output 178lm
Absolute Output 163lm

LOR 92%

Colour Temperature 3000K*


CRI 95


Optics 12X35°

Gear Type Dimmable options available

Weight 141g

* Please enquire as to the availability of non-standard colour temperatures.

























Domino 1 Basis Track is a low profile, track-mounted 95CRI architectural luminaire. The minimal aesthetic, common across the Precision portfolio, ensures the luminaire blends into its architectural surroundings. The luminaire comes as standard in brushed aluminium, and has five changeable optics for flexible distribution. The built-in, anti-reflective, magnetic accessory holder enables glare control and accommodates accessories up to 2mm thick. Domino 1 Basis Track is machined from aerospace grade 6063-T6 aluminium, delivering a lumen package of 178lm at 2.5W from its internal 24V DC driver.

Product Photometry independently tested in accordance with LM-79







Dasis Hack

BT-651-AL-3095E1



SALES@PRECISIONLIGHTING.CO.UK

42 RIVERSIDE ROAD LONDON SW17 OBA

VERTICAL ELLIPSE



Category Interior use only IP20

Material Machined Aluminium

Finish Brushed Aluminium

System Basis Track

Accessories Lenses

System Power 2.5W

Module Output 178lm

Absolute Output 163lm

LOR 92%

Colour Temperature 3000K*


CRI 95


Optics 35X12°

Gear Type Dimmable options available

Weight 141g

^{*} Please enquire as to the availability of non-standard colour temperatures.

























Domino 1 Basis Track is a low profile, track-mounted 95CRI architectural luminaire. The minimal aesthetic, common across the Precision portfolio, ensures the luminaire blends into its architectural surroundings. The luminaire comes as standard in brushed aluminium, and has five changeable optics for flexible distribution. The built-in, anti-reflective, magnetic accessory holder enables glare control and accommodates accessories up to 2mm thick. Domino 1 Basis Track is machined from aerospace grade 6063-T6 aluminium, delivering a lumen package of 178Im at 2.5W from its internal 24V DC driver.

Product Photometry independently tested in accordance with LM-79







Basis Track

BT-651-AL-3095E2



PRECISION LIGHTING

SALES@PRECISIONLIGHTING.CO.UK

42 RIVERSIDE ROAD LONDON SW17 OBA