
OCULUS 16

NARROW SPOT I LONG SNOOT




Category Interior use only IP20
Material Machined Aluminium
Finish Brushed Aluminium I Black I White I Custom
System Eutrac I Monopoint I LV tracks
Lockable Pan & Tilt
Accessories Snoots I Louvres I Lenses
System Power 9.8W
Module Output 712lm
Absolute Output 678lm
LOR 95%
Colour Temperature 3000K*
CRI Ra: 95 **TM-30** Rf: 93 Rg: 99
Optics 12°
Gear Type Dimmable options available
Weight 403g


* Please enquire as to the availability of non-standard Colour Temperatures.





Oculus 16 is a 95CRI LED spotlight, based on a highly efficient heatsink with advanced features and benefits. The spotlight comes as standard in white, black and brushed aluminium finishes, and has three site changeable optics for flexible distribution. Movement is aided with a low friction bearing rotation and constant torque tilt mechanism, both lockable in pan and tilt. The Precision Lighting Jack Plug system enables the luminaire to be easily disconnected and reconnected to all of Precision Lighting's systems, offering flexibility throughout the product's lifetime. The onboard 24V driver ensures overcurrent protection and is not polarity sensitive. Oculus 16 is machined from aerospace grade 6063-T6 aluminium, delivering a lumen package of 712lm at 9.8W.

Product Photometry independently tested in accordance with LM-79









	BT-722-AL-309512	RT-722-AL-309512	EUT3-722-AL-309512	MPS-722-AL-309512		MPX-722-AL-309512	MPY-722-AL-309512	MPZ-722-AL-309512
		RT-722-BK-309512	EUT3-722-BK-309512	MPS-722-BK-309512		MPX-722-BK-309512	MPY-722-BK-309512	MPZ-722-BK-309512
		RT-722-WH-309512	EUT3-722-WH-309512	MPS-722-WH-309512		MPX-722-WH-309512	MPY-722-WH-309512	MPZ-722-WH-309512

PRECISION LIGHTING

SALES@PRECISIONLIGHTING.CO.UK
WWW.PRECISIONLIGHTING.CO.UK

42 RIVERSIDE ROAD
LONDON SW17 0BA
t. +44 (0) 20 8947 6616
f. +44 (0) 20 8286 6626


OCULUS 16

SPOT I LONG SNOOT




Category Interior use only IP20
Material Machined Aluminium
Finish Brushed Aluminium I Black I White I Custom
System Eutrac I Monopoint I LV tracks
Lockable Pan & Tilt
Accessories Snoots I Louvres I Lenses
System Power 9.8W
Module Output 712lm
Absolute Output 678lm
LOR 95%
Colour Temperature 3000K*
CRI Ra: 95 **TM-30** Rf: 93 Rg: 99
Optics 20°
Gear Type Dimmable options available
Weight 403g


* Please enquire as to the availability of non-standard Colour Temperatures.





Oculus 16 is a 95CRI LED spotlight, based on a highly efficient heatsink with advanced features and benefits. The spotlight comes as standard in white, black and brushed aluminium finishes, and has three site changeable optics for flexible distribution. Movement is aided with a low friction bearing rotation and constant torque tilt mechanism, both lockable in pan and tilt. The Precision Lighting Jack Plug system enables the luminaire to be easily disconnected and reconnected to all of Precision Lighting's systems, offering flexibility throughout the product's lifetime. The onboard 24V driver ensures overcurrent protection and is not polarity sensitive. Oculus 16 is machined from aerospace grade 6063-T6 aluminium, delivering a lumen package of 712lm at 9.8W.

Product Photometry independently tested in accordance with LM-79









	BT-722-AL-309520	RT-722-AL-309520	EUT3-722-AL-309520	MPS-722-AL-309520		MPX-722-AL-309520	MPY-722-AL-309520	MPZ-722-AL-309520
		RT-722-BK-309520	EUT3-722-BK-309520	MPS-722-BK-309520		MPX-722-BK-309520	MPY-722-BK-309520	MPZ-722-BK-309520
		RT-722-WH-309520	EUT3-722-WH-309520	MPS-722-WH-309520		MPX-722-WH-309520	MPY-722-WH-309520	MPZ-722-WH-309520

PRECISION LIGHTING

SALES@PRECISIONLIGHTING.CO.UK
WWW.PRECISIONLIGHTING.CO.UK

42 RIVERSIDE ROAD
LONDON SW17 0BA
t. +44 (0) 20 8947 6616
f. +44 (0) 20 8286 6626


OCULUS 16

FLOOD I LONG SNOOT




Category Interior use only IP20
Material Machined Aluminium
Finish Brushed Aluminium I Black I White I Custom
System Eutrac I Monopoint I LV tracks
Lockable Pan & Tilt
Accessories Snoots I Louvres I Lenses
System Power 9.8W
Module Output 712lm
Absolute Output 672lm
LOR 94%
Colour Temperature 3000K*
CRI Ra: 95 **TM-30** Rf: 93 Rg: 99
Optics 40°
Gear Type Dimmable options available
Weight 403g


* Please enquire as to the availability of non-standard Colour Temperatures.





Oculus 16 is a 95CRI LED spotlight, based on a highly efficient heatsink with advanced features and benefits. The spotlight comes as standard in white, black and brushed aluminium finishes, and has three site changeable optics for flexible distribution. Movement is aided with a low friction bearing rotation and constant torque tilt mechanism, both lockable in pan and tilt. The Precision Lighting Jack Plug system enables the luminaire to be easily disconnected and reconnected to all of Precision Lighting's systems, offering flexibility throughout the product's lifetime. The onboard 24V driver ensures overcurrent protection and is not polarity sensitive. Oculus 16 is machined from aerospace grade 6063-T6 aluminium, delivering a lumen package of 712lm at 9.8W.

Product Photometry independently tested in accordance with LM-79









	BT-722-AL-309540	RT-722-AL-309540	EUT3-722-AL-309540	MPS-722-AL-309540		MPX-722-AL-309540	MPY-722-AL-309540	MPZ-722-AL-309540
		RT-722-BK-309540	EUT3-722-BK-309540	MPS-722-BK-309540		MPX-722-BK-309540	MPY-722-BK-309540	MPZ-722-BK-309540
		RT-722-WH-309540	EUT3-722-WH-309540	MPS-722-WH-309540		MPX-722-WH-309540	MPY-722-WH-309540	MPZ-722-WH-309540

PRECISION LIGHTING
SALES@PRECISIONLIGHTING.CO.UK
WWW.PRECISIONLIGHTING.CO.UK
42 RIVERSIDE ROAD
LONDON SW17 0BA
t. +44 (0) 20 8947 6616
f. +44 (0) 20 8286 6626