



TANA Micro

Code Table



Housing/Finish	Cover/Lens	LED Type	Colour (CCT)	Length Availability ²	IP Rating/Connection Type	Voltage
TANA Micro, Silver anodised	No cover X	504 ³	2100K	TANA Micro 352 93.3-2010mm 83.3mm increments	IP20, 1000mm Single tail	24V DC
			2300K	TANA Micro 504 110-2010mm 100mm increments	IP20, 1000mm Double tail	
		352	2500K	TANA Micro 508 81.4-2010mm 71.4mm increments	IP20, 3000mm Single tail	
			2700K	TANA Micro 207 93.3-2010mm 83.3mm increments	IP20, 3000mm Double tail	
			3000K	TANA Micro 208 176.7-2010mm 166.7mm increments		
		352	3200K			
			3500K			
			3800K			
		207 ¹	5000K			
			RED			
			GREEN			
			BLUE			
			ORANGE			
			AMBER			

¹ LEDmix requires two colour temperature choices

² When using adjustable end cap bracket, max length is limited to 1000mm

³ n-line: 2700K/3000K

Code Example:

TMSA	-	X	-	s504	-	35K	-	M	510	-	20d2	-	g
TANA Micro, Silver anodised		No cover		s-line 504		3500K		510mm		IP20, 1000mm Double tail		24V DC	

¹ LEDmix Code Example:

TMSA	-	X	-	d207	-	21	-	35	-	M	510	-	20d2	-	g
TANA Micro, Silver anodised		No cover		LEDmix 207		2100K		3500K		510mm		IP20, 1000mm Double tail		24V DC	