






Groove Light Accessories



LIGHTING ACCESSORIES




Groove Light-L accessory,
2 x 300mm (11.81") single tails, IP40 only
KKLA-01A (2700K HCRI)
KKLA-01P (3000K HCRI)





Groove Light-X accessory,
4 x 300mm (11.81") single tails, IP40 only
KKLA-02A (2700K HCRI)
KKLA-02P (3000K HCRI)

MOUNTING OPTIONS



KKCP-16 (1no.)
Clip (Allow 2 per metre/40")
Anodised aluminium finish



KKCH-01*
PVC channel (minimum 200mm (7.87") PVC channel per 500mm (19.69") of Groove Light)
Black PVC finish
* Specify length of channel in 1000mm (39.37") increments (to be cut on site further as required)

KKDC CONTROL



IP67
100W 24V
Aluminium housing
L248/W73/H48mm
(L9.76/W2.87/H1.89in)

KKPS-01 1-10V PSU*
visDIM dimmable power supply (See Control Gear)
* Not suitable for use with RGB/LEDmix



IP67
100W 24V
Aluminium housing
L248/W73/H48mm
(L9.76/W2.87/H1.89in)

KKPS-02 DMX PSU
visDIM dimmable power supply (See Control Gear)



KKDC CONTROL (CONTINUED)



IP67
100W 24V
Aluminium housing
L248/W73/H48mm
(L9.76/W2.87/H1.89in)

KKPS-03 DALI PSU

visDIM dimmable power supply (See Control Gear)



IP20
Black plastic housing
L164/W64/H34mm
(L6.46/W2.52/H1.34in)

KKDM-05 1-10V

visDIM dimmable sub-controllers (See Control Gear)



IP20
Black plastic housing
L164/W64/H34mm
(L6.46/W2.52/H1.34in)

KKSC-03A DMX (Screw terminal)

visDIM dimmable sub-controllers (See Control Gear)



IP20
Black plastic housing
L164/W64/H34mm
(L6.46/W2.52/H1.34in)

KKSC-03B DMX (RJ45)

visDIM dimmable sub-controllers (See Control Gear)



IP20
Black plastic housing
L164/W64/H34mm
(L6.46/W2.52/H1.34in)

KKDL-01 DALI

visDIM dimmable sub-controllers (See Control Gear)