



LiNi-S

Code Table



Housing/Finish	Cover/Lens	LED Type	Colour (CCT)	Length Availability	IP Rating/Connection Type	Voltage	
LiNi-S, Silver anodised LSSA	Clear cover	B	 504 ² n504	2100K 21K	LiNi-S 352 M 93.3-2014mm 83.3mm increments	IP40, 50mm Single IP20 connector 40a3	24V DC g
	Diffused cover	C	508 ² n508	2300K 23K	LiNi-S 007 M 55.7-2014mm 41.7mm increments	IP40, 50mm Double IP20 connector 40a4	
	Prismatic cover	G	 352 s352	2500K 25K	LiNi-S 504 M 114-2014mm 100mm increments	IP40, 300mm Single tail 40c1	
			007 s007	2700K 27K	LiNi-S 508 M 85.4-2014mm 71.4mm increments	IP40, 300mm Double tail 40c2	
			504 s504	3000K 30K	LiNi-S 207 M 97.3-2014mm 83.3mm increments	IP40, 300mm Single IP20 connector 40c3	
			508 s508	3200K 32K	LiNi-S 208 M 180.7-2014mm 166.7mm increments	IP40, 300mm Double IP20 connector 40c4	
			 352 e352	3500K 35K	LiNi-S RGB M 97.3-2014mm 83.3mm increments	IP40, 1000mm Single tail 40d1	
			007 e007	3800K 38K			
			504 e504	5000K 50K			
			508 e508	RED RED  s352, s007, s504 only			
		 207 ¹ d207	GREEN GRN				
		208 ¹ d208	BLUE BLU				
		 RGB d501	ORANGE ORN				
			AMBER AMB				
			RGB RGB 				

¹ LEDmix requires two colour temperature choices

² n-line: 2700K/3000K

Code Example:

LSSA	-	C	-	s504	-	35K	-	M	514	-	40c2	-	g
LiNi-S, Silver anodised		Diffused cover		s-line 504		3500K		514mm		IP40, 300mm Double tail		24V DC	

¹ LEDmix Code Example:

LSSA	-	C	-	d207	-	21	-	35	-	M	514	-	40c2	-	g
LiNi-S, Silver anodised		Diffused cover		LEDmix 207		2100K		3500K		514mm		IP40, 300mm Double tail		24V DC	