



KKSL

Code Table



Housing/Finish	LED Type	Colour (CCT)	Length Availability	IP Rating	Connection Type	Voltage
KKSL, Silver anodised SLSA	 504 ² 	2300K ¹ (2100K PCB) 	KKSL 352  99.3-2016mm 83.3mm increments	IP67 	300mm Single tail 	24V DC 
	508 ² 	2500K ¹ (2300K PCB) 	KKSL 504  116-2016mm 100mm increments		300mm Double tail 	
	 352 	3000K ¹ (2500K PCB) 	KKSL 508  87.4-2010mm 71.4mm increments		300mm Single IP67 connector 	
	504 	3400K ¹ (2700K PCB) 	KKSL RGB  99.3-2016mm 83.3mm increments		300mm Double IP67 connector 	
	508 	4000K ¹ (3000K PCB) 				
	 352 	RED  				
	504 	GREEN 				
	508 	BLUE 				
	 RGB 	ORANGE 				
		AMBER 				
		RGB  				

¹ Actual colour temperature after colour shift caused by silicone potting

² n-line: 3400K (2700K PCB)/4000K (3000K PCB)

Code Example:

SLSA	-	s504	-	40K	-	M	516	-	67	-	c7	-	8	-	g
KKSL, Silver anodised		s-line 504		4000K ¹ (3000K PCB)		516mm			IP67		300mm Single IP67 connector		Clip		24V DC