



LiNi Glow

Code Table



Housing/Finish	Cover/Lens	LED Type	Colour (CCT)	Length Availability	IP Rating/Connection Type	Voltage
LiNi Glow, Silver anodised	Diffused U cover	n- 508 ¹ n508	2100K 21K	LiNi Glow 007 M 55.7-2014mm 41.7mm increments	IP40, 50mm Single IP20 connector	24V DC g
			2300K 23K	LiNi Glow 508 M 85.4-2014mm 71.4mm increments	IP40, 50mm Double IP20 connector	40a4
		s- 007 s007	2500K 25K		IP40, 300mm Single tail	40c1
		508 s508	2700K 27K		IP40, 300mm Double tail	40c2
		e- 007 e007	3000K 30K		IP40, 300mm Single IP20 connector	40c3
		508 e508	3200K 32K		IP40, 300mm Double IP20 connector	40c4
			3500K 35K		IP40, 1000mm Single tail	40d1
			3800K 38K			
			5000K 50K			
			RED RED s- s007 only			
			GREEN GRN			
			BLUE BLU			
			ORANGE ORN			
			AMBER AMB			

¹ n-line: 2700K/3000K

Code Example:

LGSA	-	0	-	s508	-	35K	-	M	514	-	40c2	-	g
LiNi Glow, Silver anodised		Diffused U cover		s-line 508		3500K		514mm		IP40, 300mm Double tail		24V DC	