




MOUNTING OPTIONS



KKCP-11
Concealed clip
(Allow 3 per metre/40")
S/Steel finish



Anodised aluminium finish
* Cut & drilled to fit on site



KKJT-02
Joining Bar* (Allow 1 per join)
Anodised aluminium finish
* Mounting option required with
Joining Bar

22mm (0.87")

CONNECTORS



KKCN-01 50mm (1.97") pair **KKCN-03** 300mm (11.81") pair 2 PIN male + female connector set



KKCN-07 50mm (1.97") pair **KKCN-09** 300mm (11.81") pair 4 PIN RGB male + female connector set





CONNECTORS (CONTINUED)



KKCN-18 50mm (1.97") pair **KKCN-19** 300mm (11.81") pair 4 PIN LEDmix male + female connector set



KKCN-06 2 PIN 300mm (11.81") extension lead



KKCN-114 PIN RGB 300mm (11.81") extension lead



KKCN-24 4 PIN LEDmix 300mm (11.81") extension lead

KKDC CONTROL



IP67 100W 24V Aluminium housing L248/W73/H48mm (L9.76/W2.87/H1.89in)

KKPS-01 1-10V PSU* visDIM dimmable power supply (See Control Gear) * Not suitable for use with RGB/LEDmix



IP67 100W 24V Aluminium housing L248/W73/H48mm (L9.76/W2.87/H1.89in)

KKPS-02 DMX PSU visDIM dimmable power supply (See Control Gear)





KKDC CONTROL (CONTINUED)



IP67 100W 24V Aluminium housing L248/W73/H48mm (L9.76/W2.87/H1.89in)

KKPS-03 DALI PSU visDIM dimmable power supply (See Control Gear)



IP20 Black plastic housing L164/W64/H34mm (L6.46/W2.52/H1.34in)

KKSC-03A DMX (Screw terminal) visDIM dimmable sub-controllers (See Control Gear)



IP20 Black plastic housing L164/W64/H34mm (L6.46/W2.52/H1.34in)

KKDL-01 DALI visDIM dimmable sub-controllers (See Control Gear)



IP20 Black plastic housing L164/W64/H34mm (L6.46/W2.52/H1.34in)

KKDM-05 1-10V visDIM dimmable sub-controllers (See Control Gear)



IP20 Black plastic housing L164/W64/H34mm (L6.46/W2.52/H1.34in)

KKSC-03B DMX (RJ45) visDIM dimmable sub-controllers (See Control Gear)