



LiNi-S XL

Code Table



Housing/Finish	Cover/Lens	LED Type	Colour (CCT)	Length Availability	IP Rating/Connection Type	Voltage
LiNi-S XL, Silver anodised SXSA	Clear cover B	 504 ² n504	2100K 21K	LiNi-S XL 352 M 94.3-2011mm 83.3mm increments	IP40, 50mm Single IP20 connector 40a3	24V DC g
	Diffused cover C	508 ² n508	2300K 23K	LiNi-S XL 504 M 111-2011mm 100mm increments	IP40, 50mm Double IP20 connector 40a4	
		 352 s352	2500K 25K	LiNi-S XL 508 M 82.4-2011mm 71.4mm increments	IP40, 300mm Single tail 40c1	
		504 s504	2700K 27K	LiNi-S XL 207 M 94.3-2011mm 83.3mm increments	IP40, 300mm Double tail 40c2	
		508 s508	3000K 30K	LiNi-S XL 208 M 177.7-2011mm 166.7mm increments	IP40, 300mm Single IP20 connector 40c3	
		 352 e352	3200K 32K	LiNi-S XL RGB M 94.3-2011mm 83.3mm increments	IP40, 300mm Double IP20 connector 40c4	
		504 e504	3500K 35K		IP40, 1000mm Single tail 40d1	
		508 e508	3800K 38K			
		 207 ¹ d207	5000K 50K			
		208 ¹ d208	RED RED  s352, s504 only			
		 RGB d501	GREEN GRN			
			BLUE BLU			
			ORANGE ORN			
			AMBER AMB			
			RGB RGB 			

¹ LEDmix requires two colour temperature choices

² n-line: 2700K/3000K

Code Example:

SXSA	-	C	-	s504	-	35K	-	M	511	-	40c2	-	g
LiNi-S XL, Silver anodised		Diffused cover		s-line 504		3500K		511mm			IP40, 300mm Double tail		24V DC

¹ LEDmix Code Example:

SXSA	-	C	-	d207	-	21	-	35	-	M	511	-	40c2	-	g
LiNi-S XL, Silver anodised		Diffused cover		LEDmix 207		2100K		3500K		511mm			IP40, 300mm Double tail		24V DC