
Linear


LiNi Glow XL
Accessories


MOUNTING OPTIONS







KKCP-11
Concealed clip
(Allow 3 per metre/40")
S/Steel finish






KKCR-01-1000 1000mm (39.37")
KKCR-01-2000 2000mm (78.74")
KKCR-01-3000 3000mm (118.11")
Cable Raceway*
Anodised aluminium finish
* Cut & drilled to fit on site





KKJT-02
Joining Bar* (Allow 1 per join)
Anodised aluminium finish
* Mounting option required with Joining Bar

CONNECTORS



KKCN-01 50mm (1.97") pair
KKCN-03 300mm (11.81") pair
2 PIN male + female connector set




KKCN-07 50mm (1.97") pair
KKCN-09 300mm (11.81") pair
4 PIN RGB male + female connector set

Linear

LiNi Glow XL
Accessories

CONNECTORS (CONTINUED)



KKCN-18 50mm (1.97") pair
KKCN-19 300mm (11.81") pair
4 PIN LEDmix male + female connector set



KKCN-06
2 PIN 300mm (11.81") extension lead



KKCN-11
4 PIN RGB 300mm (11.81") extension lead



KKCN-24
4 PIN LEDmix 300mm (11.81") extension lead

KKDC CONTROL



IP67
100W 24V
Aluminium housing
L248/W73/H48mm
(L9.76/W2.87/H1.89in)

KKPS-01 1-10V PSU*
visDIM dimmable power supply (See Control Gear)
* Not suitable for use with RGB/LEDmix



IP67
100W 24V
Aluminium housing
L248/W73/H48mm
(L9.76/W2.87/H1.89in)

KKPS-02 DMX PSU
visDIM dimmable power supply (See Control Gear)

Linear

LiNi Glow XL
Accessories

KKDC CONTROL (CONTINUED)



IP67
100W 24V
Aluminium housing
L248/W73/H48mm
(L9.76/W2.87/H1.89in)

KKPS-03 DALI PSU
visDIM dimmable power supply (See Control Gear)



IP20
Black plastic housing
L164/W64/H34mm
(L6.46/W2.52/H1.34in)

KKDM-05 1-10V
visDIM dimmable sub-controllers (See Control Gear)



IP20
Black plastic housing
L164/W64/H34mm
(L6.46/W2.52/H1.34in)

KKSC-03A DMX (Screw terminal)
visDIM dimmable sub-controllers (See Control Gear)



IP20
Black plastic housing
L164/W64/H34mm
(L6.46/W2.52/H1.34in)

KKSC-03B DMX (RJ45)
visDIM dimmable sub-controllers (See Control Gear)



IP20
Black plastic housing
L164/W64/H34mm
(L6.46/W2.52/H1.34in)

KKDL-01 DALI
visDIM dimmable sub-controllers (See Control Gear)