



LiNi Glow XL

Code Table



Housing/Finish	Cover/Lens	LED Type	Colour (CCT)	Length Availability	IP Rating/Connection Type	Voltage	
LiNi Glow XL, Silver anodised	Diffused U cover	 504 ² n504	2100K 21K	LiNi Glow XL 352 M 94.3-2011mm 83.3mm increments	IP40, 300mm Single tail 40c1	24V DC g	
			2300K 23K	LiNi Glow XL 504 M 111-2011mm 100mm increments	IP40, 300mm Double tail 40c2		
		 352 s352	2500K 25K	LiNi Glow XL 508 M 82.4-2011mm 71.4mm increments	IP40, 300mm Single IP20 connector 40c3		
			2700K 27K	LiNi Glow XL 207 M 94.3-2011mm 83.3mm increments	IP40, 300mm Double IP20 connector 40c4		
			3000K 30K	LiNi Glow XL 208 M 177.7-2011mm 166.7mm increments	IP40, 1000mm Single tail 40d1		
		 352 e352	3200K 32K	LiNi Glow XL RGB M 94.3-2011mm 83.3mm increments			
			3500K 35K				
			3800K 38K				
		 207 ¹ d207	5000K 50K				
			208 ¹ d208				
		 RGB d501	RED RED  s352, s504 only				
			GREEN GRN				
			BLUE BLU				
			ORANGE ORN				
			AMBER AMB				
			RGB RGB 				

¹ LEDmix requires two colour temperature choices

² n-line : 2700K, 3000K

Code Example:

GXSA	-	0	-	s504	-	35K	-	M	511	-	40c2	-	g
LiNi Glow XL, Silver anodised		Diffused U cover		s-line 504		3500K		511mm		IP40, 300mm Double tail		24V DC	

¹ LEDmix Code Example:

GXSA	-	0	-	d207	-	21	-	35	-	M	511	-	40c2	-	g
LiNi Glow XL, Silver anodised		Diffused U cover		LEDmix 207		2100K		3500K		511mm		IP40, 300mm Double tail		24V DC	