






MOUNTING OPTIONS




KKCP-07
Side clip (Allow 4 per metre/40")
White plastic



KKCP-08
IP65 side clip (Allow 4 per metre/40")
Clear plastic



KKBK-14
IP65 silicone bracket
(Allow 4 per metre/40")
Translucent silicone



KKBK-18
IP65 RGB silicone bracket
(Allow 4 per metre/40")
Translucent silicone

CONNECTORS



KKCN-01 50mm (1.97") pair
KKCN-03 300mm (11.81") pair
2 PIN male + female connector set



KKCN-07 50mm (1.97") pair
KKCN-09 300mm (11.81") pair
4 PIN RGB male + female connector set



FX Accessories



CONNECTORS (CONTINUED)



KKCN-06

2 PIN 300mm (11.81") extension lead



KKCN-11

4 PIN RGB 300mm (11.81") extension lead

KKDC CONTROL



IP67
100W 24V
Aluminium housing
L248/W73/H48mm
(L9.76/W2.87/H1.89in)

KKPS-01 1-10V PSU*

visDIM dimmable power supply (See Control Gear)

* Not suitable for use with RGB/LEDmix



IP67
100W 24V
Aluminium housing
L248/W73/H48mm
(L9.76/W2.87/H1.89in)

KKPS-02 DMX PSU

visDIM dimmable power supply (See Control Gear)



IP67
100W 24V
Aluminium housing
L248/W73/H48mm
(L9.76/W2.87/H1.89in)

KKPS-03 DALI PSU

visDIM dimmable power supply (See Control Gear)



IP20
Black plastic housing
L164/W64/H34mm
(L6.46/W2.52/H1.34in)

KKDM-05 1-10V

visDIM dimmable sub-controllers (See Control Gear)



FX Accessories



KKDC CONTROL (CONTINUED)



IP20
Black plastic housing
L164/W64/H34mm
(L6.46/W2.52/H1.34in)

KKSC-03A DMX (Screw terminal)
visDIM dimmable sub-controllers (See Control Gear)



IP20
Black plastic housing
L164/W64/H34mm
(L6.46/W2.52/H1.34in)

KKSC-03B DMX (RJ45)
visDIM dimmable sub-controllers (See Control Gear)



IP20
Black plastic housing
L164/W64/H34mm
(L6.46/W2.52/H1.34in)

KKDL-01 DALI
visDIM dimmable sub-controllers (See Control Gear)