



LiNi-R XL

Code Table



Housing/Finish	Cover/Lens	LED Type	Colour (CCT)	Length Availability	IP Rating/Connection Type	Voltage
LiNi-R XL, Silver anodised	Diffused cover	352 s352	2100K 21K	LiNi-R XL 352 M 99.3-2016mm 83.3mm increments	IP40, 50mm Single IP20 connector	24V DC g
			504 s504	LiNi-R XL 504 M 116-2016mm 100mm increments	IP40, 50mm Double IP20 connector	
			508 s508	LiNi-R XL 508 M 87.4-2016mm 71.4mm increments	IP40, 300mm Single tail	
		352 e352	2700K 27K	LiNi-R XL 207 M 99.3-2016mm 83.3mm increments	IP40, 300mm Double tail	
			504 e504	LiNi-R XL 208 M 182.7-2016mm 166.7mm increments	IP40, 300mm Single IP20 connector	
			508 e508	LiNi-R XL RGB M 99.3-2016mm 83.3mm increments	IP40, 300mm Double IP20 connector	
		207 ¹ d207	3500K 35K		IP40, 1000mm Single tail	
			208 ¹ d208			
		RGB d501	5000K 50K			
			RED RED s352, s504 only			
			GREEN GRN			
			BLUE BLU			
			ORANGE ORN			
			AMBER AMB			
			RGB RGB			

¹ LEDmix requires two colour temperature choices

Code Example:

RXSA	-	C	-	s504	-	35K	-	M	516	-	40c1	-	g
LiNi-R XL, Silver anodised		Diffused cover		s-line 504		3500K		516mm		IP40, 300mm Single tail		24V DC	

¹ LEDmix Code Example:

RXSA	-	C	-	d207	-	21	-	35	-	M	516	-	40c1	-	g
LiNi-R XL, Silver anodised		Diffused cover		LEDmix 207		2100K		3500K		516mm		IP40, 300mm Single tail		24V DC	