

IP20/54	IP67/68	POWER SUPPLIES	CABLES	PROFILES	CONNECTORS	PCB COLOUR	4.91 W/M
302.3 Lm/M	CE	RoHS COMPLIANT					

■ PRODUCT SPECIFICATION


Dimension	L5000/W8mm
PCB increment	Power connection and cut point every 100mm
LED pitch	16.77mm
Chip	Epistar
Beam angle	120°
Colours	White
Bin/step	3 Step MacAdam ellipse
CRI	94.6
Lifetime	50000hrs @45°
Operating temp.	0 - 50°C
IP rating	IP20/54/67/68
Mounting	3M VHB backing tape
Minimum bend radius	10mm
Connection	Hardwire tails or male/female connectors
Control	0-10V/1-10V/DMX/DALI



■ PERFORMANCE DATA (for 1000mm)

Power consumption	4.91W
Supply voltage	24V DC
Supply current	0.205A
Luminous flux	302.3Lm/M

TECHNICAL DRAWING



PRODUCT DETAILS

Product name	ECO FLEX 60
Stated output	302.3lm per metre
Description	Flexible LED Tape, 2400K, 24V, 4.91W/m
Quantity/length of product tested	1 x 1000mm
Bin tolerance/# . MacAdams ellipse of chip	3 Step MacAdam ellipse

ELECTRICAL CHARACTERISTICS

Input Voltage (V DC)	24
Input power (WDC)	4.91
Input Current (mA DC)	205mA

LIGHT OUTPUT

Total light output (Lumens)	302.3
Luminaire efficacy (lm/W)	61.57
Beam angle	120°


COLOUR CHARACTERISTICS

Correlated colour temperature (CCT)	2350K
Colour rendering index (CRI, Ra)	94.6
Chromaticity coordinates (CIE 1931 - x,y)	0.4917, 0.4163

COLOUR RENDERING INDEX

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
95	98	99	95	95	98	93	84	68	94	97	88	96	99	91

CHROMATICITY DIAGRAM



SPECTRAL RADIANT FLUX VERSUS WAVELENGTH

