VEX-H-LINE

VEXICA

PROJECT		TYPE	
QUANTITY		LOCATION	

Luminaire:

Materials: Anodised Aluminium

Finish: Silver Anodised Body and Opal Resin

Profile Dimensions: 28 x 21mm

Lengths: 127mm to 1502mm in 125mm Increments

Accessories: ABS Fixing Clips

**Formats**: 2700K, 3000K, 3500K, 4000K, 5000K

Lens: Opal Resin Fill

Cable Entry: Rear Exit (IP76 Rated Connector) for End to End Illumination

Binning: CREE Z BIN

Technical

Wattage	2.5 Watts per 125mm	**Actual Power consumption (W)**	2.5
Driver Type Remote	Constant voltage 24 VDC	**Luminaire Lumens**	122
Driver options	SWITCHED	**Source Lumens (per DC watt)**	75
Connections	JST IP67	**Operating Temperature (°C)**	-10 to + 40
CRI (Minimum)	80	**CCT (K)**	2700
Number of LEDs	12 per 125mm	**LED Pitch (mm)**	10.4
Beam Angle (°)	160	**Listings**	CE
IP rating	IP67	**Weight (g)**	72 per 125mm
Dimensions (mm)	28 x 21mm L: 127mm		

VEXICA

Dimensions

L=125mm increments from 127mm to 1502mm

127

"L"

21

28

Product order code

VEX - H - LINE - 127 - 2700 - IP67 - SWITCHED