




**DomoLED 95 Trim - Trim**

**RD26BM11-903000D010**



90 x 90 mm

**DESCRIPTION**

Square mounting trim in cast aluminium with springs for trim installation on a ceiling thickness of max. 25mm or brackets for trimless installation on a ceiling thickness of 12-15mm. Luminaire body of formed white coated steel. Diffuser made of satin opal acrylic. Front trim/diffuser is fitted by snap-in catch action. IP44 (protection against dust and spraying water). Available in three sizes.

**MOUNTING**

Indoor Lighting - Recessed

**OPTIC**

Equipped with acrylic satin opal diffuser.

**ELECTRICAL / LED DRIVER**

D0 - No Dimming

**LIGHT SOURCE AND PERFORMANCE**

LIGHT SOURCE: LED Built-in with body - Samsung - SMD

SDCM:

CCT: 30 - 3000K

CRI: 90

SYSTEM POWER: 7.5

DELIVERED LUMEN: 524.736lm

IP: 44

Notes:



**ORDERING CODE**

Follow the steps to specify your fixture final code, example: **RE61MB13-803020DL11**

PRODUCT CODE	LIGHT SOURCE CODE	-	CRI	CCT	BEAM ANGLE (BA°)	DRIVER OPTIONS	FINISH
RD26	BM11	-	90	30 - 3000K	00	D0	10 - Black

**NOTES:**

We reserve the right to change specifications without prior notification.

HONG KONG	-	LONDON	-	MILAN	-	SHANGHAI	-	USA
-----------	---	--------	---	-------	---	----------	---	-----