




## DomoLED 180 Trim - Trim



## RD18BM11-903000D010



### DESCRIPTION

Square mounting trim in cast aluminium with springs for trim installation on a ceiling thickness of max. 25mm or brackets for trimless installation on a ceiling thickness of 12-15mm. Luminaire body of formed white coated steel. Diffuser made of satin opal acrylic. Front trim/diffuser is fitted by snap-in catch action. IP44 (protection against dust and spraying water). Available in three sizes.

### MOUNTING

Indoor Lighting - Recessed

### OPTIC

Equipped with acrylic satin opal diffuser.

### ELECTRICAL / LED DRIVER

D0 - No Dimming

### LIGHT SOURCE AND PERFORMANCE

LIGHT SOURCE: LED Built-in with body - Samsung - SMD

SDCM:

CCT: 30 - 3000K

CRI: 90

SYSTEM POWER: 22

DELIVERED LUMEN: 1336.8lm

IP: 44

Notes:



### ORDERING CODE

Follow the steps to specify your fixture final code, example: **RE61MB13-803020DL11**

PRODUCT CODE	LIGHT SOURCE CODE	-	CRI	CCT	BEAM ANGLE (BA°)	DRIVER OPTIONS	FINISH
RD18	BM11	-	90	30 - 3000K	00	D0	10 - Black

### NOTES:

We reserve the right to change specifications without prior notification.

HONG KONG	-	LONDON	-	MILAN	-	SHANGHAI	-	USA
-----------	---	--------	---	-------	---	----------	---	-----