




DomoLED 235 Trimless - Trimless

RE26BM11-904000DP11



DESCRIPTION

Square mounting trim in cast aluminium with springs for trim installation on a ceiling thickness of max. 25mm or brackets for trimless installation on a ceiling thickness of 12-15mm. Luminaire body of formed white coated steel. Diffuser made of satin opal acrylic. Front trim/diffuser is fitted by snap-in catch action. IP44 (protection against dust and spraying water). Available in three sizes.

MOUNTING

Indoor Lighting - Recessed

OPTIC

Equipped with acrylic satin opal diffuser.

ELECTRICAL / LED DRIVER

DP - Phase

LIGHT SOURCE AND PERFORMANCE

LIGHT SOURCE: LED Built-in with body - Samsung - SMD

SDCM:

CCT: 40 - 4000K

CRI: 90

SYSTEM POWER: 33.501

DELIVERED LUMEN: 2212.125lm

IP: 44

Notes:



ORDERING CODE

Follow the steps to specify your fixture final code, example: RE61MB13-803020DL11

PRODUCT CODE	LIGHT SOURCE CODE	-	CRI	CCT	BEAM ANGLE (BA°)	DRIVER OPTIONS	FINISH
RE26	BM11	-	90	40 - 4000K	00	DP	11 - White

NOTES:

We reserve the right to change specifications without prior notification.

HONG KONG	-	LONDON	-	MILAN	-	SHANGHAI	-	USA
-----------	---	--------	---	-------	---	----------	---	-----