

# THE LUX COMPANY Gola 160 Recessed Trimless Middle



#### Gola 160 Recessed Trimless Middle - Trimless



## G1MB1128-903000D010



LIGHT SOURCE:

SYSTEM POWER:

DELIVERED LUMEN: 11880lm

SDCM:

CCT:

CRI:

Notes:

LIGHT SOURCE AND PERFORMANCE



LED Built-in with body - Gola LED

Module 1128 - LED Module

30 - 3000K

90

40

80.52

## DESCRIPTION

Recessed trim or trimless linear luminaire system with installation via adjustable brackets. Luminaire housing in extruded aluminium and end caps in cast aluminium. Satin white diffuser in extruded UV heat resistant acrylic. End caps are mechanically attached with no exposed fasteners. Available in four width apertures (40-60-95-160mm) and mountable vertically or horizontally. System versions can be configured into linear, 90 ° L, T and X shapes or other custom configurations (details are all by request). Gola 95 and 160 can incorporated spotlight modules. Optional Gimbalo light head module with tiltable and routable heads for Gola 95 and 160.

# MOUNTING

Indoor Lighting - System

#### OPTIC

NOTES:

Acrylic opal white diffuser.

## ELECTRICAL / LED DRIVER

D0 - No Dimming

ORDERING CODE
Follow the steps to specify your fixture final code, example: RE61MB13-803020DL11

PRODUCT CODE LIGHT SOURCE CODE - CRI CCT BEAM ANGLE (BA°)

DRIVER OPTIONS FINISH

G1MB 1128 - 90 30 - 3000K 00 D0 10 - Black

We reserve the right to change specifications without prior notification.

HONG KONG - LONDON - MILAN - SHANGHAI - USA