






Round Recessed LED Downlight

- Round Recessed Lockable LED Downlight
- Die cast aluminium trim with extruded aluminium heat sink
- Lockable vertical tilting 0°-35° and horizontal rotation 350°
- XTM Xicato remote phosphor LED technology
- Ra81 Standard/Ra81 Vibrant colour rendering up to 5000 lumens
- 1x2 step MacAdams over life
- Ra98 Artist/Ra95 Vibrant colour rendering up to 3000 lumens
- LED module life rating at 50,000hrs L70/C3
- 5 year warranty on LED system
- Colour consistent over life
- Concealed fix option
- Dimming available
- System efficacy up to 129 lm/w
- UK design and manufacture

Colour Rendering Table

		Ra	R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
Standard Series	K	81	80	85	89	81	78	80	86	66	16	64	79	58	81	93	75
Artist Series	A	98	98	99	98	98	98	97	98	98	98	99	98	88	98	98	98
Vibrant Series V80	V	81	81	86	81	81	80	80	85	85	16	66	90	62	82	93	77
Vibrant Series V95	R	95	99	98	96	96	98	96	95	95	90	67	95	97	98	98	98



Product Code

Product	QAD	Round Recessed Lockable Downlight
Reflector Size	11T	111mm Diameter
	S	Standard Driver
	D	DALI Driver
Drivers	B	DSI Driver
	A	1-10V Dimming Driver
	T	Triac Driver
	13	1300 Lumens
	20	2000 Lumen
Lumens	30	3000 Lumen
	40	4000 Lumen
	50	5000 Lumen
	27	2700 Kelvin
Colour Temperature	30	3000 Kelvin
	35	3500 Kelvin
	40	4000 Kelvin
	K	Ra81 Standard
RA (Colour Rendering)	A	Ra98 Artist Series
	V	Ra81 Vibrant
	R	Ra95 Vibrant
Beam Angle (9mm LES)	10	10° Twist-Lock Reflector*
	15	15° Reflector
Beam Angle (19mm LES)	30	30° Reflector
	40	40° Reflector
	W	White
Body Colour	B	Black
	G	Grey
	0	No Attachment
	1	3 Hour Emergency Pack
Extras	2	Self-Test 3 Hour Emergency Pack
	3	3 Hours Emergency DALI EM Pro
	5	Concealed Fix
	6	Concealed Fix c/w Emergency Pack

* max 2000lm 9mm LES

XICATO® **CE**

