



RGB 60 ULTRA BRIGHT

The RGB Ultra Bright delivers vibrant colours from a high quality SMD 5050 Chip. The Ultra Bright range offers a wide variety of colour choices alongside a balanced design for efficiency and performance. The RGB Ultra Bright Flex is ideally suited to any application where colour is needed. The extensive colour palette will complement all applications.

SPECIFICATIONS

POWER CONSUMPTION

14.4 W/M | 0.6 A | DC


CUTTING INTERVALS

24V 6 LED 100MM

OPERATING TEMPERATURE

0 - 50°C

PRODUCT OPTIONS



Power Supplies

Cables

Profiles

Connectors

PCB Colour

TECHNICAL DATA


IP OPTIONS	DIMENSIONS (mm)	PACKAGE WEIGHT	PACKAGE SIZE (mm)	LED TYPE	LIFESPAN	POWER SOURCE	PRODUCT LENGTH	DIMMABLE	ENERGY CONSUMPTION	EFFICIENCY CLASS	CRI	BEAM ANGLE
IP 20	2.05 x 10	155g	235 x 210 x 10	SMD CHIP 5050	5 YEARS	24 VDC	5M	YES	1.4 KWh/1000h	A++	-	120°
IP 65	4.7 x 12	493g	250 x 240 x 16									

PRODUCT TYPE


COLOUR	VOLTAGE	IP RATING	LED QTY/M	WATTAGE/M	COLOUR TEMPERATURE	LUMINOUS EFFICIENCY	LUMEN/M	DOMINANT WAVELENGTH (nm)	PITCH MM	SKU
RGB	24V	20	60	14.4	-	58-75Lm/W	840-1080	R625 G525 B465	16.67mm	010-0301
RGB	24V	65	60	14.4	-	58-75Lm/W	840-1080	R625 G525 B465	16.67mm	010-0302

PRODUCT DIMENSIONS

IP20



IP65



LUMEN OUTPUT

