

ULTRA INTENSE 60

Ultra Intense 60 LED Flex is the flagship product of the LED Flex range, Ultra Intense uses an innovative design, keeping running costs low, whilst producing high light output and light quality, The Ultra Intense range is the most popular LED Flex on the market today. We also offer this LED Flex in a waterproof IP rated coating for outdoor applications.

SPECIFICATIONS

POWER CONSUMPTION

10 W/M | 0.42 A | DC

CUTTING INTERVALS

24V 6 LED 100MM

OPERATING TEMPERATURE

0 - 50°C

PRODUCT OPTIONS













Power Supplies

Cables Profiles Connectors

PCB Colour

PRODUCT DIMENSIONS





LUMEN OUTPUT



TECHNICAL DATA

IP OPTIONS	DIMENSIONS (mm)	PACKAGE WEIGHT	PACKAGE SIZE (mm)	LED TYPE	LIFESPAN	POWER SOURCE	PRODUCT LENGTH	DIMMABLE	ENERGY CONSUMPTION	EFFICIENCY CLASS	CRI	BEAM ANGLE
IP 20	1.5 x 8	100g	240 x 210 x 10	SMD CHIP 3328	5 YEARS	24 VDC	5M	YES	1 KW/h/1000h	A++	80+	120°
IP 65	4.5 x 10.5	376g	255 x 240 x 15									

PRODUCT TYPE

COLOUR	VOLTAGE	IP RATING	LED QTY/M	WATTAGE/M	COLOUR TEMPERATURE	LUMINOUS EFFICIENCY	LUMEN/M	DOMINANT WAVELENGTH (nm)	PITCH MM	SKU
PURE WHITE	24V	20	60	10	5000K	130Lm/W	1380	-	16.67mm	010-0701
PURE WHITE	24V	65	60	10	5000K	130Lm/W	1380	-	16.67mm	010-0702
NATURAL W	24V	20	60	10	4000K	130Lm/W	1380	-	16.67mm	010-0707
NATURAL W	24V	65	60	10	4000K	130Lm/W	1380	-	16.67mm	010-0708
WARM WHITE	24V	20	60	10	2700K	130Lm/W	1380	-	16.67mm	010-0703
WARM WHITE	24V	65	60	10	2700K	130Lm/W	1380	=	16.67mm	010-0704

