



# EYECONIC SQUARE WALL WASH

STANDARD

PHOS.CO.UK +44 208 492 7633



Project Ref.

Luminaire Ref.

Date

# EYECONIC SQUARE WALL WASH - STANDARD

The Eyeconic Square Wall Wash is a recessed, fixed downlight with a 80x80mm square bezel, wall wash lens and a discrete removeable anti-glare guard.

### **PRODUCT FEATURES**

Downlight

Fixed

Interior

LED

IP65

Available in all Phos finishes

Interchangeable optics & accessories (pre & post install)

### PHOS STANDARDS

60min fire-certified

Acoustic-rated

UK designed, manufactured and assembled

5 year warranty

### **OPTICS**

Standard beam angles:

Wall Wash

### PHYSICAL PROPERTIES

Diameter Ø80mm

Height 73mm (4W/9W)

Height 98mm (14W)

Cut-out ø56mm


#### **DRIVER INFORMATION**


Driver Configurator (Link)

### **PRODUCT VIEW**



### **DIMENSIONS**





4W & 9W

14W



Accessories

# TECHNICAL SPECIFICATIONS


ССТ	2700K									
Wattage	4W	9W	14W							
Beam Angles	WW	WW	WW							
Luminaire Lumens (lm)	125	211	262							
Circuit Watts (c/W)	6	10.8	16.2							
Luminaire Efficacy (l/cW)	21	20	16							
Luminance (Cd)	147	243	309							
Forward Voltage (Vf)	11.78	12.36	12.65							
Current (mA)	350	700	1050							
ССТ	3000K									
	4044									
Wattage	4W	9W	14W							
Beam Angles	WW	WW	WW							
Luminaire Lumens (lm)	131	232	302							
Circuit Watts (c/W)	6	10.8	16.3							
Luminaire Efficacy (l/cW)	22	21	18							
Luminace (Cd)	155	268	354							
Forward Voltage (Vf)	11.78	12.36	12.65							
Current (mA)	350	700	1050							
Binning		2 stan MacAdams								
CRI	2 step MacAdams									
TM-30-15	90+ Rg 101 Rf 90									
Lumen Maintenance	kg 101 ki 90 LM80									
Lifetime	50,000 hours									
Dimming Options	Mains dim / Non-dim / 0-10V / DALI (dim to dark 0.01%) / Casambi									
Flicker Index	0									
SVM: (Visual Flicker)	0.02									
Driver distance from fitting	Up to 10m (AWG 20)*									
Wiring Type	Series									

\*If driver distance from fitting is +10m see driver configurator document for guidance


Remote emergency (Maintained / Self Test)



# LIGHT CONES



# **POLAR CURVES**



# PARTCODE BUILDER

### Example Code: EY-SQW-WT/B1-STD14-30-90-WW-1050

\*Codes for custom finishes can be found on the page 6.

Family	Variant	Bezel Finish	Socket Finish	Engine	Power	ССТ	CRI	Beam Angle	Driver Current
<b>EY</b> Eyeconic	<b>SQW</b> Square Wall Wash	WT White Textured		<b>STD</b> Standard	<b>4</b> Watts	<b>27</b> 2700K	90	WW	350
		B1 Anodised Black *C			<b>9</b> Watts	<b>30</b> 3000K			700
		Custom			<b>14</b> Watts				1050



### **FINISHES**

Every element of your light can be finished in any of the options below:

### PLATED (Interior ONLY)



Antique Bronze 01



**Antique Brass** 02



Polished Chrome 03



Satin Nickel 04



**Polished Copper** 05



Satin Copper 06



Polished Brass 09

#### ANODISED (Interior ONLY, except Orba Exteriors)



Tuba Brass



Antique Gold



Espresso Bronze



Cocoa Bronze



Ice Gold 15



Mocha Bronze 16



Taupe Bronze 17



24K Gold 18



Champagne Gold 19



Anodised Black (9005) В1

### POWDER COAT (Interior & Exterior)



Pure White (9010) **W1** 



WT

Textured Black (9005) BT



**RAL Classic** www.phos.co.uk/finishes



RAL Design price on application