

COBE H

Profile with optic
Profil aluminium avec optique

A3962




Puissance maxi **Power max**
33 w/m

Dimensions **Dimensions**
30 x 18 mm

Longueur maximale **Max.length**
3000 mm

Température d'utilisation **Ambiant temp.**
- 10°C / + 40°C



A3962.C9.IP20.00.OP.DALI

Type of led

| | |
|----------------|-------|
| Pure CRI99 | A4199 |
| UltraCRI | A4101 |
| Dynamic White | A4102 |
| Regular | A4109 |
| RGB | A4106 |
| RGB+W | A4107 |
| RGB+2W | A4117 |
| High Efficacy | A4111 |
| Ultra Efficacy | A4116 |

C99
CR
DW
C9
RGB
RGBW
RGB2W
HE
UE

IP Rating

| |
|-------------|
| IP20 |
| IP54 |
| IP65H |
| IP65R Resin |

IP20
IP54
IP65
IP65R

Finishes

| |
|---------------------------|
| Aluminium anodised silver |
| Aluminium anodised black |
| Painting RAL |

00
04
RAL

Cover & Optic

| |
|-----------|
| Opal |
| Frost |
| Frost 30° |
| Aluminium |

OP
FR
F30
AL

Dimming

| |
|-----------------------|
| No dimming |
| Dali |
| Dmx |
| Dimming & to 10Vdc |
| Phase Dimming Digital |

HF
DALI
DMX
D10
PHD



A3962.04



A3962.SUS -
Clips Inox