


Cobra Flex Chain

Adjustable in 3 directions



Body

Surface mounted modular system in extruded aluminium, LED links connected by a steel wire enabling adjustment of each individual LED link in 3 directions.

Available in different length configurations based on a 54mm link (2 LED per link) with a 64mm increment. Section 28.5 x 30mm. Its flexible structure maintain a constant 30mm pitch between the LED.

Mounting options:
U mounting clips.

*** Plastic free packaging.**

Accessories

Honeycomb Art. 2D88.
Color filter Art. 2E40.
Mounting accessories included.
Power extension cable Art. 2C47 to be ordered separately.

Finish

Anodized black, white, brass polished or gold finish.
Other finish options available on request.

LED sources

Power LED.
CRI: 75 & 90 | R9: >90 | CCT: 2100K, 2400K, 2700K, 3000K, 3500K, 4000K.
3-Step MacAdam.
Other CRI and CCT options available on request.

Optic

Lens.
Beam angle: 10° / 17° / 29° / elliptical (15° x 50°).
Wallwasher optics.

Driver

Driver not included to be ordered separately.
Work with 1050 mA Constant Current Driver positioned remotely.

Applications

Ideal for indirect cove illumination, it creates a wall grazing effect for columns and curved architectonic surfaces. Its flexible structure maintain a constant pitch between LED, insuring a continuous illumination without any shadows or dark areas. Application areas: Cove light, wallwash, residential, hospitality, restaurants, museums.

Related Products

Cobra Linealuce 

Cobra Flex 

Cobra Linealuce Louvre 

Cobra Flex Louvre 

Cobra Flex Chain Louvre 

Cobra Pro IP66 




Cobra Flex Chain | G472

Cobra
Flex Chain




Min. L= 54mm (2 x LED) 1 Link




Mounting options

With mounting U clip




Accessories


Honeycomb Art. 2D88



Adjustable



Max. L= 1014mm (32 x LED) 16 Links



Available length codes ¹

No. of Links	Voltage	LED Power	Length code	Length in mm	Length in inches	Nominal Lumen	No. of Links	Voltage	LED Power	Length code	Length in mm	Length in inches	Nominal Lumen
1	3.3V	3.1W	0054	54	2.12	366 lm	9	29.7V	28.3W	0566	566	22.28	3294 lm
2	6.6V	6.3W	0118	118	4.65	732 lm	10	33V	31.5W	0630	630	24.80	3660 lm
3	9.9V	9.4W	0182	182	7.17	1098 lm	11	36.3V	34.6W	0694	694	27.32	4026 lm
4	13.2V	12.6W	0246	246	9.69	1464 lm	12	39.6V	37.8W	0758	758	29.84	4392 lm
5	16.5V	15.7W	0310	310	12.20	1830 lm	13	42.9V	40.9W	0822	822	32.36	4758 lm
6	19.8V	18.9W	0374	374	14.72	2196 lm	14	46.2V	44.1W	0886	886	34.88	5124 lm
7	23.1V	22W	0438	438	17.24	2562 lm	15	49.5V	47.2W	0950	950	37.40	5490 lm
8	26.4V	25.2W	0502	502	19.76	2928 lm	16	52.8V	50.4W	1014	1014	39.92	5856 lm

Code ordering example: **G 4 7 2 0 0 5 4 - 9 0 2 7 1 0 0 0 1 0**

	Product code*	Length code	>CRI	CCT**	LED Power	Nominal Lumen	Beam angle (BA°)	Driver Options	Finish	
Cobra Flex Chain	G472	Min. 0054	90	27 2700K	1.5W/LED	183lm/LED	10 / 17 / 29 / EL / WW	00 No Driver	10 ■ Black	
		⋮		30 3000K					11 □ White	
		Max. 1014		35 3500K					28 ■ Brass Polished	
				40 4000K					35 ■ Gold	
				75 21 2100K					173lm/LED	
				24 2400K						

Notes:


¹ Information in the chart above is related to 3000K LED.

Driver Options

Constant Current

Cobra Flex Chain

2C02 Constant Current LED Driver. 1 Driver can drive 2-32LEDs, about 954mm Max.




G472

Power extension cable. Art. **2C47**. 1m (if necessary).

Vin= 180-277V AC 50/60Hz
 Iout= 1050mA V=2~57V
 P= 60W Max.
 Dimensions: 123.5x81.5x23mm
 IP20

Accessories



Product / Accessories

Honeycomb

Coloured Filters

Finish: 10

Filter colour codes: 25 / 42 / 55 / 85

Cobra Flex Chain


2D88

2E40-25
2E40-42
2E40-55
2E40-85

* Please refer to the user manuals for further details.

Cobra Flex Chain Louvre

Adjustable in 3 directions



Body

Surface mounted modular system in extruded aluminium, LED links connected by a steel wire enabling adjustment of each individual LED link in 3 directions.

Available in different length configurations based on a 54mm link (2 LED per link) with a 64mm increment. Section 28.5 x 30mm. Its flexible structure maintain a constant 30mm pitch between the LED. Integrated louvre.

Mounting options:
U mounting clips.

*** Plastic free packaging.**

Accessories

Mounting accessories included.
Power extension cable Art. 2C47 to be ordered separately.

Finish

Anodized black, white, brass polished or gold finish.
Other finish options available on request.

LED sources

Power LED.
CRI: 75 & 90 | R9: >50 | CCT: 2100K, 2400K, 2700K, 3000K, 3500K, 4000K.
3-Step MacAdam.
Other CRI and CCT options available on request.

Optic

Lens.
Beam angle: 10° / 17° / 29° / elliptical (15° x 50°).
Wallwasher optics.

Driver

Driver not included to be ordered separately.
Work with 1050 mA Constant Current Driver positioned remotely.

Applications

Ideal for indirect cove illumination, it creates a wall grazing effect for columns and curved architectonic surfaces. Its flexible structure maintain a constant pitch between LED, insuring a continuous illumination without any shadows or dark areas. Application areas: Cove light, wallwash, residential, hospitality, restaurants, museums.

Related Products

Cobra Linealuce 

Cobra Flex 

Cobra Flex Chain 

Cobra Linealuce Louvre 

Cobra Flex Louvre 

Cobra Pro IP66 




Cobra Flex Chain Louvre | G473

Cobra
Flex Chain
Louvre




Min. L= 54mm (2 x LED) 1 Link




Mounting options


With mounting U clip



Adjustable



Max. L= 1014mm (32 x LED) 16 Links



Available length codes ¹

No. of Links	Voltage	LED Power	Length code	Length in mm	Length in inches	Nominal Lumen	No. of Links	Voltage	LED Power	Length code	Length in mm	Length in inches	Nominal Lumen
1	3.3V	3.1W	0054	54	2.12	366 lm	9	29.7V	28.3W	0566	566	22.28	3294 lm
2	6.6V	6.3W	0118	118	4.65	732 lm	10	33V	31.5W	0630	630	24.80	3660 lm
3	9.9V	9.4W	0182	182	7.17	1098 lm	11	36.3V	34.6W	0694	694	27.32	4026 lm
4	13.2V	12.6W	0246	246	9.69	1464 lm	12	39.6V	37.8W	0758	758	29.84	4392 lm
5	16.5V	15.7W	0310	310	12.20	1830 lm	13	42.9V	40.9W	0822	822	32.36	4758 lm
6	19.8V	18.9W	0374	374	14.72	2196 lm	14	46.2V	44.1W	0886	886	34.88	5124 lm
7	23.1V	22W	0438	438	17.24	2562 lm	15	49.5V	47.2W	0950	950	37.40	5490 lm
8	26.4V	25.2W	0502	502	19.76	2928 lm	16	52.8V	50.4W	1014	1014	39.92	5856 lm

Code ordering example: **G 4 7 3 0 0 5 4 - 9 0 2 7 1 0 0 0 1 0**

	Product code*	Length code	>CRI	CCT**	LED Power	Nominal Lumen	Beam angle (BA°)	Driver Options	Finish
Cobra Flex Chain Louvre	G473	Min. 0054	90	27 2700K	1.5W/LED	183lm/LED	10 / 17 / 29 / EL / WW	00 No Driver	10 ■ Black
		⋮		30 3000K					11 □ White
		Max. 1014		35 3500K					28 ■ Brass Polished
				40 4000K					35 ■ Gold
				75 2100K					
				24 2400K					

Notes:

¹ Information in the chart above is related to 3000K LED.

Driver Options


Constant Current

Cobra Flex Chain Louvre



L
N
Dim

Art. 2C02D0 (On/Off)
Art. 2C02D1 (0-10V)
Art. 2C02DA (DALI)



G473

Power extension cable. Art. **2C47**. 1m (if necessary).

Vin= 180-277V AC 50/60Hz
Iout= 1050mA V=2-57V
P= 60W Max.
Dimensions: 123.5x81.5x23mm
IP20