

MT50LEDAC INTEGRAL DRIVER

Suspended/Surface mounted. Tubular LED light, with aluminium end caps.

A CLASSIC LED FITTING.

The MT50 LED AC is a clean-cut classic design LED fitting. The satin or clear diffusers will enhance any modern space. The lights can be suspended horizontally or surface mounted. The cylindrical tube offers a 180° distribution of light through its polycarbonate diffuser.

The MT50 LED AC is an incredibly versatile linear lighting solution, it makes use of efficient LED technology offering switched or Dali dimming options for a controllable level of light output.

Suitable for almost any interior application.

- Light Source Information
- LED/Electronic Driver.
- Available in 3000K & 4000K.

Options

- 3hr Emergency with Dali monitoring.
- Available as through wired and plug and go.
- Aluminium end caps as standard.
- Anodised end caps available in many more colours including black, rose gold and brass (see right).

Emergency available from size 4 upwards, HE only.

Cat No.	Length (mm)	Lumens Clear	Lumens Satin	Circuit Power (W)
HIGH EFFICIENCY				
MT50 LED 2 HE AC	582	1250	1340	12
MT50 LED 3 HE AC	862	1950	1820	15
MT50 LED 4 HE AC	1142	2600	2040	20
MT50 LED 5 HE AC	1422	3410	3640	23
MT50 LED 6 HE AC	1702	4045	3670	27
MT50 LED 7 HE AC	1982	4700	4510	31
MT50 LED 8 HE AC	2262	5190	5260	34
HIGH OUTPUT				
MT50 LED 2 HO AC	582	3015	2555	19
MT50 LED 3 HO AC	862	3690	4190	27
MT50 LED 4 HO AC	1142	5240	5400	35
MT50 LED 5 HO AC	1422	5630	6590	43
MT50 LED 6 HO AC	1702	6765	8015	49
MT50 LED 7 HO AC	1982	8810	8110	60
MT50 LED 8 HO AC	2262	9680	9680	65

Dimming 1-10V or Dali.

Installation

Horizontal, angled suspension or surface mounted.

Optics

Satin or clear polycarbonate diffuser.



Available End Cap colours



Suspension Kit



Plastic & Stainless Steel Clamps



Light output 180°

For further information Call: +44 (0)1525 376974 Email: reply@encapsulite.co.uk or visit www.encapsulite.co.uk