


ULTRA EFFICIENCY 90

Linear strip with high efficiency >180 lm/w and CRI90

Ruban haute efficacité >180 lm/w et IRC90

A4190



Temperature de couleur CCT

2200K - 2400K - 2700K - 3000K - 3500K - 4000K - 5000K - 6000K - 6500K

Precision de couleur & IRC Color consistency & CRI OneBinOnly | >90

Rendement lumineux Luminous Efficacy (@4000K) >180 lm/w

Puissance & nombre de led Power & number of Led 21.6 w/m | 15 w/m | 10w/m & 240 leds/m


Coupe Cutting unit 33.33 mm

Dimensions Dimensions 5000 x 10 x 1.2 mm

Tension d'alimentation & Classe isolation Input voltage & Class 24Vdc I class III

Température d'utilisation Ambient temperature - 10°C / + 40°C

10/15/21.6w



Cutting unit



A4190.22.240.927.IP20.DALI

Power & number leds/m

21.6 w/m & 240 leds/m

15 w/m & 240 leds/m

10 w/m & 240 leds/m

Custom power on request

22.240

15.240

10.240

CCT & luminous flux/m

	10w/lm	15w/lm	21.6wlm	
2200K	1026 lm	2215 lm	3190 lm	922
2400K	1063 lm	2295 lm	3305 lm	924
2700K	1126 lm	2431 lm	3501 lm	927
3000K	1188 lm	2566 lm	3695 lm	930
3500K	1188 lm	2566 lm	3695 lm	935
4000K	1251 lm	2701 lm	3890 lm	940
5000K	1251 lm	2701 lm	3890 lm	950
6000K	1251 lm	2701 lm	3890 lm	960
6500K	1251 lm	2701 lm	3890 lm	965

IP Rating

IP20

IP54 (Wet indoor)

Pour des IP supérieur, veuillez nous consulter

For higher IP ratings, please contact us.

IP20

IP54

Dimming

No dimming

Dali

Dmx

Dimming 0/1-10V

Casambi

HF

DALI

DMX

D10

CSB